

---

Subject: Re: Reading unformatted data from exabyte tape  
Posted by [Fergus Gallagher](#) on Wed, 12 Apr 1995 07:00:00 GMT  
[View Forum Message](#) <> [Reply to Message](#)

---

Dennis Lee Hlavka <[sgdlh@virl.gsfc.nasa.gov](mailto:sgdlh@virl.gsfc.nasa.gov)> wrote:

> I'm trying to find a way to read unformatted data from an exabyte tape  
> using readu. The problem is the data is structured with a lonarr  
> header of 50 words followed by a data array (fltarr of 6620 words).  
> I can read each record successfully if I only read the header or  
> the data alone (ie lonarr(6670) or fltarr(6670). I hope there is  
> a way that I can read both in the same record in IDL. Any  
> suggestions?

Sounds like a similar situation to when the data are written by F77. F77 adds checksum longwords at the start and end of each record and so you have to account for this if the data are read without the /F77 flag in openr.

If this is not relevant, please supply a few more details.

Fergus

```
=====
| Fergus Gallagher           |
| Remote Sensing Applications Development Unit |
| British National Space Centre       |
| Monks Wood                     |
| Huntingdon PE17 2LS / UK          |
|                               |
| F.Gallagher@nerc.ac.uk          |
| http://uh.nmt.ac.uk/bnsc/fgg.html |
=====
```

---