

---

Subject: Re: z-buffer and /noerase ?

Posted by [btt](#) on Tue, 09 Nov 2004 17:43:52 GMT

[View Forum Message](#) <> [Reply to Message](#)

---

sandrokan wrote:

> Ave, IDL users!

>

> I've got two contour maps that should be drawn over an image, and I'm using  
> contour with /noerase key.

>

> One could expect that the second contour would be drawn over the first one.

> Strangely, if I use "set\_plot, 'z'" command, the order is reversed (the

> first one is over the second one). Please see this code:

>

>

>

> pro test3

> device, decomposed=0

> loadct, 13

> set\_plot, 'z'

> erase

> a=dist(50) gt 10

> contour, a, levels=[.5], color=200, /noerase

>

> contour, a-1, levels=[-.5], color=100, /noerase

>

> a=tvrd()

> set\_plot, 'win'

>

> tv, a

> end

>

>

> I got a yello line (color=200) instead of the plue line (color=100).

> This problem does not happen if I use the win device....

>

>

> Thank you very much for any explanation. I use IDL5.2...

>

>

> A

>

>

Hi,

Try switching z-buffering off (I think it is sticky, so don't forget to turn it  
back on which is the default.)

DEVCIIE, z\_buffering = 0

Ben

---