
Subject: Re: Line-Mouse widget tool

Posted by [Robert Barnett](#) on Tue, 29 Mar 2005 22:42:59 GMT

[View Forum Message](#) <> [Reply to Message](#)

David,

I render a direct graphics plot onto a widget_draw.

How do you transform a mouse click event which is specified in pixels to data-space when using direct graphics? I can compute it from the xmargin, ymargin, xtick_get, ytick_get, xsize and ysize. But, surely there must be an easier way?

Here is an excerpt from my code:

```
; ev - The event struct
; draw_id - The Widget_Draw
; return_keywords - Keywords returned from plot

xcharsize = 6.0
ycharsize = 10.0

geometry = widget_info(self.draw_id, /geometry)

; Calculate the corresponding x,y value coordinate on the plot
evx = ev.x - xmargin[0] * xcharsize
evy = ev.y - ymargin[0] * ycharsize
evwidth = geometry.xsize - total(xmargin) * xcharsize
evheight = geometry.ysize - total(ymargin) * ycharsize

xtickget = *return_keywords.xtick_get
ytickget = *return_keywords.ytick_get

xmaxtick = N_ELEMENTS(xtickget) - 1
ymaxtick = N_ELEMENTS(ytickget) - 1
x = xtickget[0] + (xtickget[xmaxtick] - xtickget[0]) * evx / evwidth
y = ytickget[0] + (ytickget[ymaxtick] - ytickget[0]) * evy / evheight

return, [x, y]
```

David Fanning wrote:

> Howard S. Cohl writes:

>

>

>> Oh, one more thing, if it's not too difficult, is to build into the

>> widget the capability to use curved line segments (splines, or polynomials
>> perhaps) as well as straight lines and be able to output either the
>> equation of the curve or output a the numerical set of N values for the
>> curved line segment.

>>

>

> Oh, well, a little more than an hour, then. :-)

>

> Cheers,

>

> David

>

>

--

nrb@

Robbie Barnett

imag

Research Assistant

wsahs

Nuclear Medicine & Ultrasound

nsw

Westmead Hospital

gov

Sydney Australia

au

+61 2 9845 7223
