
Subject: Re: array of pointers inside a structure
Posted by [Antonio Santiago](#) on Fri, 10 Jun 2005 18:16:01 GMT
[View Forum Message](#) <> [Reply to Message](#)

Francois L. wrote:

```
> Hello,  
>  
> I am defining a structure:  
>  
>> a = 5  
>> struct = {A:a, B:intarr(a),C:ptrarr(a)}  
>  
>  
> Further, I want the first element of the array of pointers (C[0]) to be an  
> array of 5x5 elements.  
>  
> How do I create it ?  
>  
> Thank you,  
>  
> Fran ois Leduc  
>  
>
```

```
struct = {A:a, B:intarr(a),C:ptrarr(a)}
```

'struct' is a STRUCT.
'struct.c' is an array of pointers.
'struct.c[0]' is the first element of the array of pointer.

struct.c[0] = PTR_NEW(INTARR(5,5)) Now the first element of the
pointer array (a pointer), points to an integer array.

```
IDL> a=5  
IDL> struct = {A:a, B:intarr(a),C:ptrarr(a)}  
IDL> struct.c[0] = PTR_NEW( INTARR(5,5) )  
IDL> help, struct.c[0]  
<Expression>  POINTER  = <PtrHeapVar2>  
IDL> help, *struct.c[0]  
<PtrHeapVar2>  INT      = Array[5, 5]  
IDL>
```

Also you can create a intarr variable and point c[0] to it:

```
m = INTARR(5,5)  
struct.c[0] = PTR_NEW(m)
```

But remember that PTR_NEW makes a copy of your data into the HEAP

memory. The /NO_COPY keyword creates a copy into HEAP memory and then undefines the original variable.

--

Antonio Santiago Piñerez
(email: santiago<<at>>grahi.upc.edu)
(www: http://www.grahi.upc.edu/santiago)
(www: http://asantiago.blogspot.org)

GRAHI - Grup de Recerca Aplicada en Hidrometeorologia
Universitat Politècnica de Catalunya
