
Subject: Re: CVS and IDL - RCS tags

Posted by [Paolo Grigis](#) on Mon, 11 Jul 2005 14:09:02 GMT

[View Forum Message](#) <> [Reply to Message](#)

What happens if you do a "cvs commit" after the update?

--Paolo

Ben Panter wrote:

> Rob wrote:

>

>> We have been able to do this by making this a comment in the header

>> part of the code prior to adding and committing:

>>

>> ;\$Id: \$

>>

>> When you look at it after committing it then you should see the version

>> info filled in for you. One might look like the following:

>>

>> ; \$Id: cw_color_button.pro,v 1.16 2005/07/06 16:34:25 rdimeo Exp \$

>

>

> Thanks for your help, I'm afraid I'm still not getting it!

>

> OK - I must be doing something wrong here. I'm using eclipse, so I open

> the file and edit it. I add the string that you suggested half way

> through the file:

>

> ;\$Id: \$

>

> then save the file and commit it to the archive.

>

> I then log into one of my other machines, and do a CVS update:

>

> [bdp@obrero1 bdp]\$ cvs update moped

> cvs server: Updating moped

> cvs server: Updating moped/BULK

> cvs server: Updating moped/DEEP2

> cvs server: Updating moped/GDDS

> cvs server: Updating moped/GOODS

> cvs server: Updating moped/HR

> U moped/HR/hr_setup.pro

> cvs server: Updating moped/KM

> cvs server: Updating moped/SPEC_IDL

> cvs server: Updating moped/TOOLS

>

> and indeed, hr_setup.pro has been updated, but still reads:

>

> ;\$Id: \$
>
> at the line I changed.
>
> Any suggestions?
>
