Subject: Re: CVS and IDL - RCS tags Posted by Paolo Grigis on Mon, 11 Jul 2005 14:09:02 GMT

View Forum Message <> Reply to Message

What happens if you do a "cvs commit" after the update?

--Paolo Ben Panter wrote: > Rob wrote: >> We have been able to do this by making this a comment in the header >> part of the code prior to adding and committing: >> >> ;\$Id: \$ >> >> When you look at it after committing it then you should see the version >> info filled in for you. One might look like the following: >> >> ; \$Id: cw_color_button.pro,v 1.16 2005/07/06 16:34:25 rdimeo Exp \$ > > Thanks for your help, I'm afraid I'm still not getting it! > OK - I must be doing something wrong here. I'm using eclipse, so I open > the file and edit it. I add the string that you suggested half way through the file: > ;\$Id: \$ > > then save the file and commit it to the archive. I then log into one of my other machines, and do a CVS update: > [bdp@obrero1 bdp]\$ cvs update moped > cvs server: Updating moped > cvs server: Updating moped/BULK > cvs server: Updating moped/DEEP2 > cvs server: Updating moped/GDDS > cvs server: Updating moped/GOODS > cvs server: Updating moped/HR > U moped/HR/hr_setup.pro > cvs server: Updating moped/KM > cvs server: Updating moped/SPEC_IDL cvs server: Updating moped/TOOLS > > > and indeed, hr setup.pro has been updated, but still reads:

>

```
> ;$Id: $
> at the line I changed.
> Any suggestions?
```