
Subject: Re: CASE statments
Posted by [rep2857](#) on Tue, 20 Jun 1995 07:00:00 GMT
[View Forum Message](#) <> [Reply to Message](#)

Cc'd to wart@dice.ugcs.caltech.edu

In article <3s7iea\$t60@gap.cco.caltech.edu>,
Wart <wart@dice.ugcs.caltech.edu> wrote:
> Is there any way to associate more than one tag with a set of
> instructions: Something like
>
> CASE event.id OF
>
> red_text: BEGIN
> ; do lots of stuff here
> END
...
> CASE event.id OF
>
> red_text: grn_text: blu_text: BEGIN
> ; do lots of stuff here
> END
> ENDCASE

Yup. Here you go:

```
Case 1 of
  (Event.id eq red_text or $
    Event.id eq grn_text or $
    Event.id eq blu_text): begin
    ; stuff
  end
Endcase
```

The "1" in the opening case line acts as a "true". The first statement that evaluates to true/1 will be run.

Mike Schienle Hughes Santa Barbara Research Center
Home: mgs@seldon.terminus.com Coromar Drive, M/S B28/87
Work: rep2857@sbsun0010.sbrc.hac.com Goleta, CA 93117
Contract Employee. Will visualize data for large amounts of money.
