
Subject: Re: Adobe 7.0 in IDL
Posted by [savoie](#) on Tue, 25 Oct 2005 20:00:29 GMT
[View Forum Message](#) <> [Reply to Message](#)

Steve.Morris@libero.it writes:

>> Try the command: M-x browse-url <enter: http://google.com> and see
>> what happens first.
> Thanks, this is now set :))

Good. That's got to work before anything else will.

> I have gone to customization and then set up lynx-emacs in Browse Url
> Browser Function.

> But still, I cannot manage to open the online help!
> If I put the following line in my .emacs

> (setq idlwave-help-browser-function 'lynx-emacs-browse-url)
> or this one
> (setq idlwave-help-browser-function 'lynx-browse-url)

> What's wrong??? Say I want use lynx what should I do?

O.k. I'm starting to grasp at straws. But try customizing the variable,
rather than setq'ing it.

M-x customize-variable <ret> idlwave-help-browser-function <ret>

try "browse-url-firefox" in the value, then use the state button to save it.

If this works, and brings up the help menu when doing idlwave-context-help
(also known as: "M-?"). in a firefox browser, we have the idlwave help stuff
setup correctly. Then you'll just have to try to get the lynx command

You say that you got the browse-url to work with lynx-emacs, so I'm going to
guess (I don't have lynx).

that if you customize the idlwave-help-browser-function to be
"browse-url-lynx-emacs"

You should get the behavior you are looking for.

Let's see what happens.

Matt

--

Matthew Savoie - Scientific Programmer
National Snow and Ice Data Center
(303) 735-0785 <http://nsidc.org>
