
Subject: Re: Keyword_Set function

Posted by [wmconnolley](#) on Fri, 04 Nov 2005 08:55:53 GMT

[View Forum Message](#) <> [Reply to Message](#)

David Fanning <david@dfanning.com> wrote:

> shi_lee@hotmail.com writes:

```
>> PRO d_vectrack, $
>>     state, $
>>     LOADDATA=fname, $
>>     WIDTH = fWidth, $
>>     RECORD_TO_FILENAME=record_to_filename, $
>>     GROUP=group, $           ; IN: (opt) group identifier
>>     DEBUG=debug, $          ; IN: (opt)
>>     APPTLB = appTLB, $       ; OUT: (opt) TLB of this
>> application
>>     INITIALIZE = initialize
>>     REDRAW = redraw
```

> I think I would put a comma and line continuation character

> after the INITIALIZE keyword. :-)

How dull. Wouldn't it be more entertaining to re-write the
parser to understand this code... its perfectly clear to humans what
was meant :-)))

-W.

--

William M Connolley | wmc@bas.ac.uk | <http://www.antarctica.ac.uk/met/wmc/>
Climate Modeller, British Antarctic Survey | Disclaimer: I speak for myself
I'm a .signature virus! copy me into your .signature file & help me spread!
