
Subject: Re: help with text widget...

Posted by [David Fanning](#) on Fri, 10 Feb 2006 04:05:59 GMT

[View Forum Message](#) <> [Reply to Message](#)

Steve writes:

> I'm just starting to learn how to use widgets, and am having a little
> trouble getting a text widget to display properly. I am trying to
> avoid using absolute sizing, and would prefer to let IDL size the
> widget based on the base it's in...
>
> If I use:
> base=widget_base(column=1)
> text=widget_text(base, "line1 of text")
>
> I get a nice single line output...
>
> However, what I want is to have a widget that is blank until I need to
> print to it,
> then have it print
>
> Line 1 of text
> Line 2 of text
> Line 3 of text
>
> inside the widget. I'd like the blank initial widget to be sized
> correctly to handle 3 lines of text, without actually having any text
> displayed, or without having the widget change size. Also, as I noted
> before, I would like to avoid specifying the size of the widget in
> absolute terms (i.e. # pixels), but saying it "should be 3 lines high"
> would be great...
>
> An acceptable solution (although not as good as the above) would be to
> initially print the lines when the widget is created. However, I can't
> even get this to work. If I use newline characters, these simply print
> on the line, and the result is still just a single line.
>
> Any help would be appreciated...

I agree you don't want to size the text widget in pixel sizes, probably.
But XSIZE applies to "character units" (a nebulous unit that requires
some experience to get right), and YSIZE refers to how many lines of
output you want. So something like this usually works for me:

```
textID = Widget_Text(tlb, XSize=String(Replicate(32B, 50), YSize=3)
```

Cheers,

David

--

David Fanning, Ph.D.

Fanning Software Consulting, Inc.

Coyote's Guide to IDL Programming: <http://www.dfanning.com/>
