Subject: Re: Unix to Vax floating point conversion Posted by thompson on Wed, 16 Aug 1995 07:00:00 GMT

View Forum Message <> Reply to Message

"R. David Baker" <rbaker> writes:

- > We are using PVWave Version 5.0 on a VMS Vax, and need to read in IEEE
- > binary from a Sun Sparc2. We tried to use the CONV_UNIX_VAX procedure
- > from the IDL Astronomy User's Library
- > (http://idlastro.gsfc.nasa.gov/contents.html), but didn't get it to
- > work correctly. Here's what we did:
- get_lun,unit >
- openr,unit,filename >
- readu,unit,i,t ; i is an integer to read the Sun Fortran >
- ; header and t is a floating point array >
- free lun,unit >
- ---> show unconverted numbers <-- THIS IS THE PROBLEM > print.t
- CONV UNIX VAX,t,source arch='sparc'
- print,t ---> show converted numbers

The problem was probably generated when you tried to print out the numbers before converting them. As Wayne Landsman (landsman@sorbet.gsfc.nasa.gov) points out from the IDL documentation

- > "VAX Warning: Do not attempt to interpret an XDR (=Sparc) format
- > floating-point number as a native floating number on a VAX. VAXen generate
- > an illegal instruction trap when the CPU encounters illegal floating point
- Under VAX/VMS the illegal value is automatically replaced with
- > zero and execution continues."

When you tried to print it out, you caused the computer to try to interpret it, thus generating the problem. Since it's a VAX/VMS problem, and not an IDL one, the same behavior should be seen in PVWave. The proper sequence should be

```
get lun, unit
openr,unit,filename
readu,unit,i,t
free lun,unit
CONV UNIX VAX,t,source arch='sparc'
print,t
```

Wayne goes on to say,

> So the trick to doing the number conversions is to alway deal with bytes and > never interpret an XDR number on a VAX.

I'm not sure what is meant here about always dealing with bytes. As long as

one converts the numbers into the host representation immediately after reading them, you should be okay.

He also says,

- > ... In IDL Vax V4.0 there was a bug in
- > the /FTOXDR keyword, and another bug prevented one from even subscripting an
- > XDR number on a Vax. (Note: these bugs will be fixed in the next release of
- > IDL Vax VMS V4.0.1.).

This makes me mad. This is not the first time that bugs have been introduced into IDL's BYTEORDER routine on DEC computers. It is absolutely vital for us that data is written out to files in a host independent format. We use NFS to distribute this data to a variety of computer platforms. THE BYTEORDER ROUTINE IN IDL MUST WORK!

Wayne ends with,

- > Note that none of the above problems apply to Alpha VMS machines, which
- > are considerably less finicky.

Well, thank god for that. That explains why we haven't run into this bug. (We haven't been so lucky in the past.)

Bill Thompson