

---

Subject: Re: iPlot and applications

Posted by [D. Alterman](#) on Tue, 08 Aug 2006 22:03:41 GMT

[View Forum Message](#) <> [Reply to Message](#)

---

That did the trick, thanks. And it added a mere 1.8MB to the .sav file.

-D

Benjamin Hornberger wrote:

> D. Alterman wrote:

>> I would like to create a new iPlot from within an application. I have  
>> no problem doing this from within the development environment, but when  
>> I create a .sav file for distribution and run it from the virtual  
>> machine I get the following error:

>>  
>> "Attempt to call undefined procedure/function:  
>> 'IDLITPARAMETERSET\_DEFINE'."

>>  
>> I can create a new plot window graphical object, but I would like to  
>> give the user all the functionality of iPlot to modify the graph.

>>  
>> I'm using Windows XP both for development and running the virtual  
>> machine.

>>  
>> Thank you for your help.

>> -D

>>

>

> Hi -D,

>

> the iTools code doesn't get compiled into the .sav file (RESOLVE\_ALL  
> doesn't do this). You have to do ITRESOLVE before writing out the .sav  
> file (e.g., by putting that command into your "make" file, if you  
> happened to have one), which compiles \*all\* iTools related code. In my  
> experience, this adds about 6 MB to the .sav (on Windows).

>

> Cheers,  
> Benjamin