
Subject: mbar and event handlers

Posted by [Runar Jjrgensen](#) on Wed, 06 Dec 1995 08:00:00 GMT

[View Forum Message](#) <> [Reply to Message](#)

I'm having some problems with eventhandlers and mbar. I'll illustrate with some sample code:

First the event handler. Then the widget creating routine.

```
PRO menu_base_Event, Event
widget_control, Event.Id, GET_UVALUE=Ev
```

```
.
.
end
```

```
PRO root
ROOT = widget_base(mbar=menu_base,...)
HelpMenuDesc = [...]
HelpMenu = cw_pdmnu(menu_base, /mbar, HelpMenuDesc,...)
```

```
widget_control, root, /realize
xmanager, 'menu_base', menu_base
end
```

This works fine, but then I want to add a couple of new buttons in a sub_base of ROOT. This is were everything goes wrong.

```
sub_base = widget_base(ROOT)
button=widget_button(sub_base,...)
```

The button does not recognize sub_base nor ROOT. Do I need an additional eventhandler for these buttons?

Runar Jxrgensen

```
-----
Runar Jorgensen      ||
University of Oslo   || Phone: +47 2285 5663
Department of Physics || Telefax: +47 2285 5671
P.O.Box 1048 Blindern || email: runar.jorgensen@fys.uio.no
0313 Oslo; Norway    ||
-----
```