
Subject: Re: exposing variables to higher program levels
Posted by [David Fanning](#) on Thu, 17 May 2007 11:41:24 GMT
[View Forum Message](#) <> [Reply to Message](#)

Lasse Clausen writes:

```
> So I tried:  
>  
> pro example2  
>   example  
>   print, haha  
> end  
>  
> pro example  
>   void = scope_varfetch('haha', /enter, level=-1)  
>   void = 'Hello'  
> end  
>  
> But alas!:  
> IDL> example2  
> IDL: Variable is undefined: <No name>.  
> IDL: Execution halted at: EXAMPLE      7 /home/lbnc1/idl/  
> example.pro  
> IDL:           EXAMPLE2      2 /home/lbnc1/idl/  
> example.pro  
> IDL:           $MAIN$  
>  
>  
> What am I doing wrong? Is that not exactly, what Chris wants?
```

You need to read that article again:

http://www.dfanning.com/tips/access_main_vars.html

Here is code (written with proper naming convention, BTW) that works:

```
pro example  
(scope_varfetch('haha', /enter, level=-1)) = 'Hello'  
end  
  
pro example2  
  example  
  print, haha  
end
```

And then,

IDL> example2

Hello

Cheers,

David

--

David Fanning, Ph.D.

Fanning Software Consulting, Inc.

Coyote's Guide to IDL Programming: <http://www.dfanning.com/>

Sepore ma de ni thui. ("Perhaps thou speakest truth.")
