
Subject: Re: Putting the cursor in a field
Posted by [steinhh](#) on Wed, 17 Jan 1996 08:00:00 GMT
[View Forum Message](#) <> [Reply to Message](#)

In article <19960116.172716.831183.NETNEWS@WVNVM.WVNET.EDU>, mbrown@olie.wvitcoe.wvnet.edu (Myron Brown) writes:

|>
|> Hi. I'm looking for a way to display the cursor inside
|> a field when the field is displayed. I'm using CW_FIELD
|> to create the field. The user has to place the cursor
|> inside the field by clicking the mouse button inside the
|> field. It would be nice if he didn't have to. This seems
|> like an easy thing to do; I just can't find out how. Could
|> someone help me?
|>

Using WIDGET_CONTROL,TEXT_WIDGET_ID,/INPUT_FOCUS sets the keyboard input focus to the specified text widget (same effect as clicking inside the field).

In order to get the widget ID of the text widget inside the compound field widget, the source code indicates the following should work, (given that FIELD_ID is the Widget ID of the compound, as returned by CW_FIELD):

```
LABEL_ID = WIDGET_INFO(FIELD_ID,/CHILD)
TEXT_WIDGET_ID = WIDGET_INFO(LABEL_ID,/SIBLING)
```

Stein Vidar
