
Subject: Re: for loop is killing me

Posted by [tarequeaziz](#) on Tue, 06 Nov 2007 15:29:07 GMT

[View Forum Message](#) <> [Reply to Message](#)

On Nov 6, 8:23 am, Conor <cmanc...@gmail.com> wrote:

> On Nov 6, 1:31 am, tarequea...@gmail.com wrote:

```
>
>> Hello all,
>
>> help me! I am running a code 'infested' with for loops. And as u can
>> guess, its painfully slow. The part of my code with loop looks like
>> the following:
>
>> jump1:
>
>> ;Setting up the Green functions array which will have the same number
>> of elements as of amp_vec
>
>> G=fltarr(n_elements(amp_vec),n_elements(amp_vec))
>> G_phi=fltarr(n_elements(amp_vec))
>> G_rp=fltarr(n_elements(amp_vec))
>> G_r=fltarr(n_elements(amp_vec))
>> G_in=fltarr(n_elements(amp_vec))
>> G_out=fltarr(n_elements(amp_vec))
>> G_p=fltarr(n_elements(amp_vec))
>> G_h=fltarr(n_elements(amp_vec))
>> gp=fltarr(n_elements(amp_vec))
>> gh=fltarr(n_elements(amp_vec))
>> G_in_msum = fltarr(n_elements(amp_vec))
>> G_out_msum = fltarr(n_elements(amp_vec))
>> G_in_phisum = fltarr(n_elements(amp_vec))
>> G_out_phisum = fltarr(n_elements(amp_vec))
>
>> if ignore_reldata eq 1. then begin
>>     amp_vec= abs(randomn(0.5,n_radial_points,/double))
>>     a=1.
>>     ;print,' amp_vec is',amp_vec
>> endif
>
>> do_u_like_to_start_with_rp_loop = 0 ; Set 1 if YES,0 if NO
>
>> if do_u_like_to_start_with_rp_loop eq 1. then BEGIN
>>     PRINT,' WE ARE USING rp PREFERRED LOOP'
>>     goto,jump2
>
>> ENDIF
>
>> PRINT,' WE ARE USING r PREFERRED LOOP'
```

```

>>      for i_r= 0,n_radial_points-1 do begin
>
>>          loop_time = systime(1)
>
>>          if ignore_realdata eq 1. then begin
>
>>              r_scld=( i_r*2.)/(n_radial_points -1) ;-----> We took off
>> trap radius from here for scaling purpose,see note
>
>> ;-----> Also note the use of factor 2. This is because, we
>> want to get values outside ;-----> the cylinder. But
>> this is just for demonstration purpose!!!!
>
>>          endif else begin
>
>>              r_scld=( i_r)/(n_radial_points -1) ; took off the factor 2
>
>>          endelse
>>          :r_scld = 2.
>
>>          ;print,'r_scld value is ',r_scld
>
>>          for i_rp= 0,n_radial_points-1 do begin
>
>>              if ignore_realdata eq 1. then begin
>
>>                  rp_mat = randomn(1,n_radial_points,/double)
>>                  ;print,'rp_mat is',rp_mat
>
>>                  rp_scld = rp_mat(i_rp)
>
>>              endif else begin
>
>>                  ;rp_scld=( i_rp/((n_radial_points-1))) * float(amp_vec(i_rp))
>>                  rp_scld= float(amp_vec(i_rp))
>>                  ;print,' amp_vec is',amp_vec
>
>>              endelse
>
>>              ;      rp_scld=( i_rp/((n_radial_points-1))) * float(amp_vec(i_rp))
>
>>              ;rp_mat = randomn(1,n_radial_points,/double)
>>              ; print,'rp_mat is',rp_mat
>
>>              ;rp_scld = rp_mat(i_rp)
>
>>          ;rp_scld = 0.5

```

```

>
>>          ;;print,'rp_scld for i_rp= ',i_rp,' is, ',rp_scld
>
>>          if (r_scld gt rp_scld) then begin
>>              r_plus = r_scld
>>              r_minus = rp_scld
>>          endif else begin
>>              r_minus = r_scld
>>              r_plus = rp_scld
>>          endelse
>
>
>>          ;print,'r_plus value is ',r_plus
>>          ;print,'r_minus value is ',r_minus
>
>>          for i_m=1,20 do begin      ;n_radial_points do begin
>
>>              ;;print,'starting i_m value is ',i_m
>
>>              ;if    (n_radial_points le 5) then i_phi_max = 20 else i_phi_max
>
>=
>> n_radial_points
>>          ;print,'i phi max is = ',i_phi_max
>>          i_phi_max = 20.
>
>>          for i_phi=0,i_phi_max - 1 do begin
>>              ; print,'starting i_phi value is',i_phi
>
>>              count= i_phi + 1.
>>              ;print,'count is ',count
>>              phi=(count*2*!PI)/(i_phi_max)
>
>>              ;    print,'phi value is= ',phi
>>              ;    phi= 0.785398163 ;<----- In radian
>
>>              a= 1. ; -----> Scaled trap radius
>
>>              gp(i_phi) = 2.0*(1./i_m)*(r_minus/r_plus)^i_m *
>>              gh(i_phi) = 2.0*(1./i_m)*(r_minus *
>>              r_plus/a^2)^i_m *
>>              cos(i_m*(phi))
>
>>              ;print,'cos(i_m*phi) is',cos(i_m*phi)
>
>>              ;if (i_r eq 0.) && (i_rp eq 0.) && (i_m eq 1.) then
begin
>
>>              ;print,' the 1st gp is ',gp(i_phi)

```

```

>> ;print,' the 1st gh is ',gh(i_phi)
>> ;endif
>
>> ;if ( i_r eq n_radial_points - 1.) && ( i_rp eq
>> n_radial_points -1.) && ( i_m eq n_radial_points -1.) then begin
>
>> ;print,' the Last gp is ',gp(i_phi)
>> ;print,' the Last gh is ',gh(i_phi)
>
>> ;endif
>
>> endfor ; end of phi loop
>
>> G_in_phisum [i_m -1] = total(gp) ; Add up the phi
elements
>> for a specific m
>> G_out_phisum [i_m -1] = total(gh)
>
>> endfor ; end of m-loop
>
>> G_in_msum(i_rp) = total(G_in_phisum) ; Add up all m values for
>> a specific rp value
>> G_out_msum(i_rp) = total(G_out_phisum)
>
>> G_in(i_rp) = -alog((r_plus)^2.) + G_in_msum[i_rp]
>> G_out(i_rp) = -alog((a^2./rp_sclD)^2.) + G_out_msum[i_rp]
>
>> ;print,'G_in is',G_in
>> ;print,'G_out is',G_out
>
>> G(i_r,i_rp)= G_in(i_rp) - G_out(i_rp) - alog((a/rp_sclD)^2.)
>
>> index=where(finite(G,/NaN) ,count)
>> ;print,' index is ',index
>> if (count ne 0) then G[index] = 0.
>> ;non_zero = where(G,count)
>> ;print,'non zero value is',non_zero
>> ;
>> if count ne 0. then G = G[non_zero]
>
>> ;print,' last log part',alog((a/rp_sclD)^2.)
>> ;print,' G_in - G_out is ',G_in - G_out
>> ;print,'G inside rp loop is ',G(i_r,i_rp),' for i_r =',i_r,
>> and i_rp ='i_rp
>
>> endfor ;end of rp loop
>
>> ;G_p= G_in

```

```

>> :G_h= G_out
>> ;print,'G_p is',G_p,'and G_h is',G_h
>> ;G(i_r,i_rp)= G_p(i_rp) - G_h(i_rp) - alog((a/rp_sclD)^2.)
>
>> ;print,'rp_sclD is ',rp_sclD
>
>> ;      print,' G inside the r loop is',G
>
>> ;      if i_r eq (n_radial_points-1) then print,'Last r_sclD value is',
>> r_sclD
>
>> ;if i_r eq ( (n_radial_points-1)/10.) then print,'First 1/10th
>> r_sclD value is=', r_sclD
>> ;if i_r eq ( (n_radial_points-1)/2.) then print,'First 1/2th
>> r_sclD value is=', r_sclD
>> ;if i_r eq ( (n_radial_points-1)*3./4.) then print,'3/4 th r_sclD
>> value is=', r_sclD
>> ;if i_r eq (n_radial_points-1) then print,'Last r_sclD value is',
>> r_sclD
>
>> if i_r eq (n_radial_points - 1.) then begin
>
>>     print,'The time it took to finish ',i_r,'th loop is', systime(1) -
>> loop_time,'seconds'
>
>> endif
>
>> endfor ; end of r loop
>
>> ;print,'here is the PROFILER report for r prefered loop'
>
>> ;print,'G is ',G    ;[n_radial_points - 1]
>
>> if ignore_reldata eq 1 then begin
>
>>     r_vec=(findgen(n_radial_points)/(n_radial_points))
>>     potential=fltarr(n_radial_points)
>>     prod = fltarr(n_radial_points)
>
>> endif else begin
>
>>     r_vec=(findgen(n_theta_points)/(n_theta_points))
>>     potential=fltarr(n_theta_points)
>>     prod = fltarr(n_theta_points)
>> endelse
>
>> if ignore_reldata eq 1 then p= n_radial_points else p= n_theta_points
>

```

```

>>      for k = 0,100 do begin ;p -1 do begin
>>          ;rp_mat = randomn(1,n_radial_points,/double)
>>          ;print,' amp_vec is',amp_vec
>>          ;print,'amp_vec is',amp_vec[k]
>>          ;print,'G[* ,k] is',G[* ,k]
>>              prod =amp_vec[k] * G(*,k)
>>              prod_invfft = abs( fft(prod,/inverse))
>>              potential[k] = int_tabulated(r_vec,prod_invfft)
>>          ;print,'potential is',potential
>
>> =====
>> So as u can see there are 4 for loops running. the m loop with
>> running index i_m should be 200. But setting it to 200 slows down the
>> program.
>
>> My supervisor said that, this should be a very fast way of calculating
>> green function than the traditional way(which my group-mate is doing).
>
>> what I am doing wrong?
>> Any help will be HIGHLY appreciated!
>
>> Best,
>
>> Tareque
>
> Looking back over your code again, I noticed that your whole code
> looks like essentially one big nested set of for loops. Of course,
> nested for loops are a bit harder to separate from eachother. In
> general when you are trying to optimize nested for loops the trick is
> to start from the inside and work your way out. Looking at your phi
> loop (which seems to be the innermost loop) I would do something like
> this. Your code says (getting rid of comments and empty space):
>
> for i_phi=0,i_phi_max - 1 do begin
>     count= i_phi + 1.
>     phi=(count*2*!PI)/(i_phi_max)
>     a= 1
>     gp(i_phi) = 2.0*(1./i_m)*(r_minus/r_plus)^i_m *cos(i_m*(phi))
>     gh(i_phi) = 2.0*(1./i_m)*(r_minus * r_plus/a^2)^i_m *cos(i_m*(phi))
> endfor
>
> That can be re-written:
>
> phis = findgen(i_phi_max)+1
> gp = 2.0*(1./i_m)*(r_minus/r_plus)^i_m * cos(i_m * phis*2*!PI/
> i_phi_max )
> gh = 2.0*(1./i_m)*(r_minus*r_plus/a^2)^i_m * cos(i_m * phis*2*!PI/
> i_phi_max )

```

>
> and your for loop is gone (assuming that I got everything right), as
> long as i_m, r_minus, r_plus, and a are all simple variables, and not
> arrays. I have to go to class now, so you'll have to do without any
> additional comments.

Thank u thank u thank u thank u....or may be I should write a program
which should keep sending u 'thank u' note for rest of your life!

You guys are awesome!!!!!!

Tareque
