
Subject: Re: Putting the cursor in a field
Posted by [ps](#) on Wed, 24 Jan 1996 08:00:00 GMT
[View Forum Message](#) <> [Reply to Message](#)

In article <4do4ab\$ndt@ratatosk.uio.no>,
steinhh@amon.uio.no (Stein Vidar Hagfors Haugan) writes:

> The TVCRS procedure can be used to move the mouse cursor anywhere,
> even outside the (possibly unmapped) currently selected draw window.
>
> The following example should demonstrate this:
>
> base = widget_base(/row)
> text = widget_text(base,xsize=100)
> dummy= widget_base(base,map=0)
> draw = widget_draw(dummy,xsize=1,ysize=1)
> widget_control,base,/realize
> widget_control,draw,get_value=window
> wset,window
> tvcrs,-200,-20,/device
> widget_control,text,/input_focus
>
> You just have to match the X,Y device coordinates to where you want the
> mouse cursor to appear.

Uuh, oh, that's a **very** dirty trick. However, I'll give it a try.
Thanks for the suggestion.

Peter

~~~~~  
~~~~~  
Peter "Pit" Suetterlin <http://www.kis.uni-freiburg.de/~ps>
Kiepenheuer Institut fuer Sonnenphysik
Tel.: +49 761 3198-210 ps@kis.uni-freiburg.de
-- * -- * ...-- * -- * ...-- * -- * ...-- * -- * ...-- * -- * ...-- * --
Come and see the stars! <http://www.kis.uni-freiburg.de/~ps/SFB>
Sternfreunde Breisgau e.V.
Tel.: +49 761 73571 or 278588
