
Subject: Re: Inverse Map Projection Help
Posted by [mankoff](#) on Wed, 27 Feb 2008 02:12:13 GMT
[View Forum Message](#) <> [Reply to Message](#)

On Feb 26, 7:43 am, David Fanning <n...@dfanning.com> wrote:

> mankoff writes:
>> It does help. Image is better aligned. But still not accurate :(.
>
> I just got back to my office and I'm doing the usual
> up-at-3AM-thing for a week or so. Do you mean "not accurate"
> in the way using the UV-BOX from the map structure, rather
> from the MAP_PROJ_IMAGE UV-BOX, is not accurate? This wouldn't
> surprise me. Did you try using MAP_PROJ_IMAGE for creating
> the UV-BOX, as I outlined in my article?
>
> If you make the data available, I'll schedule an appointment
> for tomorrow at 4AM. :-)
>
> Cheers,
>
> David
> --
> David Fanning, Ph.D.
> Fanning Software Consulting, Inc.
> Coyote's Guide to IDL Programming:<http://www.dfanning.com/>
> Sepore ma de ni thui. ("Perhaps thou speakest truth.")

Here is the data set website:

http://www.antarctica.ac.uk/bas_research/data/access/bedmap/download/

And the actual one I've started with is:

http://www.antarctica.ac.uk/bas_research/data/access/bedmap/download/surface.asc.gz

Code to read in this file (once un-gzipped) is:

```
pro load_asc, file, data0, data1, img
  if not keyword_set(file) then begin
    print, 'bathy, bedelev, groundbed, icethic, surface, water'
    return
  end
  result = read_ascii(file+'.asc',data_start=6)
  data0 = result.field0001
  bad = where( data0 eq -9999, complement=good )
  data1 = data0 & data1[bad] = !values.f_nan
  mm = minmax( data0[good] )
  img = bytscl( data1, min=mm[0], max=mm[1], top=253 ) + 1
  img[ bad ] = 0
```

end

My code to attempt to 'unroll' this data is above in this thread, and re-pasted here (slightly different than above perhaps... 2 days later). Note that I have uv_box from both map_proj_init and map_proj_image. I think the map_proj_image code provides slightly better match. It appears to mach East/West perfectly (?) but there is still a north/south error.

pro unroll_foo

end

;; load the data

load_asc,'surface', data & save, data

;restore

data = reverse(data,2)

x0 = -2713600 ; from data set header

y0 = -2304000

xx = [x0,x0,-1*x0,-1*x0] ; the four corners

yy = [y0,-1*y0,-1*y0,y0]

;; this is the projection the data is distributed on

stereo = map_proj_init('Polar Stereographic', /GCTP, DATUM=8, \$
 CENTER_LONGITUDE=0, CENTER_LATITUDE=-71)

lonlat = MAP_PROJ_INVERSE(xx, yy, MAP_STRUCTURE=stereo)

longitude = reform(lonlat[0,*])

latitude = reform(lonlat[1,*])

;; output zoom

limit = [-90, -180, max(latitude), 180]

;limit = [-80, 150, -70, 180]

;; this is the projection I would like it on

cyl = map_proj_init('Cylindrical', limit=limit)

range = [x0, y0, -1*x0, -1*y0]

warp = MAP_PROJ_IMAGE(data, range, \$
 image_structure= stereo, \$;; input
 map_structure = cyl, \$;; output
 missing = -2, \$
 uvrange = uvrage, \$
 min_value = 0, \$
 _EXTRA=e)

```
erase
tv, congrid( warp, !d.x_size, !d.y_size )

pos = [0,0,1,1]
;; Pick one. Which one?
uv_box = cyl.uv_box
uv_box = uvrange

Plot, uv_box[[0, 2]], uv_box[[1, 3]], Position=pos, $
    /Nodata, XStyle=5, YStyle=5, /NoErase

MAP_CONTINENTS, Map_Structure=cyl, /HIRES
map_grid, gline=0, color=255, /label, map_structure=cyl

end
```
