
Subject: Convolving speed issue

Posted by [rogass](#) on Thu, 17 Apr 2008 16:29:50 GMT

[View Forum Message](#) <> [Reply to Message](#)

Hi there,

I have a strange problem with the IDL convolving possibilities. I'd like to make a script which convolves 2 matrices - e.g. a and b - in the same behavior `conv2(a,b,'same')` Matlab does. The Problem is not to make such a script, the problem is that IDL takes too long or hangs when i try to convolve larger matrices. I tried certainly all kinds of using the built-in IDL-convol method, but convolving large arrays ends always in different results compared to the very fast Matlab `conv2`. Maybe someone could help me. Here's the sample code:

```
function size_dim, in, direction
dims = size(in, /dimensions)
return, dims[direction]
end
```

```
function zeropadding, in,xsize,ysize
;only for 2D-arrays
xsize_in=size_dim(in,0)
ysize_in=size_dim(in,1)
shiftx = ceil((xsize-xsize_in)/2)
shifty = ceil((ysize-ysize_in)/2)
temp = fltarr(xsize,ysize)
temp[0:xsize_in-1,0:ysize_in-1] = in
temp = shift(temp,shiftx,shifty)
return, temp
end
```

```
function conv2, a,b
size_a=[size_dim(a,0),size_dim(a,1)]
size_b=[size_dim(b,0),size_dim(b,1)]
a=zeropadding(a,size_a[0]+size_b[0], size_a[1]+size_b[1])
b=zeropadding(b,size_a[0]+size_b[0], size_a[1]+size_b[1])
c=fltarr(size_a[0]+size_b[0], size_a[1]+size_b[1], /nozero)
addx = floor(total(size_a)/4)
endx = ceil(double(total(size_a)/4))
addy = floor(total(size_b)/4)
endy = ceil(double(total(size_b)/4))
```

```
for n1=0,size_a[0]+size_b[0]-1 do begin
  for n2=0,size_a[1]+size_b[1]-1 do begin
    temp=0
    temp2=0
    for k1=0+addx,size_a[0]+size_b[0]-1-endx do begin
      for k2=0+addy,size_a[1]+size_b[1]-1-endy do begin
```

```

    if n1-k1 gt-1 and n2-k2 gt-1 then begin
        temp=a[k1,k2]*b[n1-k1+addx,n2-k2+addy]
        temp2=temp2+temp
    endif
endfor
endfor
c[n1,n2]=temp2
endfor
endfor
temp = shift(c,-2*addx,-2*addy)
return, temp[0:size_a[0]-1,0:size_b[0]-1]
end

```

```

pro conv
; sample matrix -> magic(5) in Matlab
a= [[17, 24, 1, 8, 15],$
    [23, 5, 7, 14, 16],$
    [4, 6, 13, 20, 22],$
    [10, 12, 19, 21, 3],$
    [11, 18, 25, 2, 9]]
b=2*a
c=a
d=b
print, 'Trying own convolution...',string(10b),conv2(a,b), string(10B)
print, 'Trying built in convolution...',string(10b),$
shift(convol(zeropadding(c,10,10),zeropadding(d,10,10), center=0,/
edge_wrap),-4,-4),string(10b)
end

```

Maybe there is a solution for using reform in some way? It seems to be quicker as for-loops. But I can't imagine how it could work when the indices of the multiplying matrices are varying.

Hope on help

Thank you and best regards

Chris
