Subject: Re: Where O Where Di My Pointer Go? Posted by phillipbitzer on Tue, 15 Jul 2008 19:43:00 GMT View Forum Message <> Reply to Message

/begin long string of curse words.....

Thanks David, that did the trick. Oh, since I bought your book, I was looking at OpenImage.pro :-)

```
On Jul 15, 2:32 pm, David Fanning <n...@dfanning.com> wrote:
> phillipbit...@gmail.com writes:
>> I've battling with this for a week now, and I think it needs a fresh
>> pair of eyes. I am working on code that pops up a Modal Widget, does
>> some manipulation, and pass some information back to the user. For
>> reference, I am using D Fanning's general approach to this problem.
I think you are going to have to look at textbox.pro just
> a little more carefully. :-)
>
    filter_dialog_info = {filter_times:PTR_NEW(times), $
                 filter data:PTR NEW(data), $
                 filter data1:PTR NEW(data), $
>>
                 filter_data2:PTR_NEW(data), $
>>
                 filter_data3:PTR_NEW(data)}
>>
>
>> WIDGET_CONTROL, tlb, SET_UVALUE=filter_dialog_info, /No_copy
  Your pointers are in a structure that you store in the UVALUE
> of your TLB. This structure is completely and utterly destroyed
> by the time you get to the other side of your XMANAGER call.
> And, while the pointers are there, you have no way to get to
> them now.
> Make your pointers outside this structure, *then* put them
> in the structure. That way, you will have access to them
  when you need them.
>
  Cheers,
>
> David
> David Fanning, Ph.D.
> Fanning Software Consulting, Inc.
> Coyote's Guide to IDL Programming (www.dfanning.com)
> Sepore ma de ni thui. ("Perhaps thou speakest truth.")
```