Subject: Re: Philosophical Question about NAN Posted by R.Bauer on Tue, 18 Nov 2008 08:18:31 GMT

View Forum Message <> Reply to Message

Paolo schrieb:

- > On the other hand,
- > NAN works much better than fixed values for
- > plots! (for instance, if nan=!values.f_nan
- > a=[1.0,2,nan,4,2]
- > will give a much better plot than if nan=-999,
- > even if one has a good yrange).

>

- > Ciao,
- > Paolo

the same is true for Inf values

```
inf = 1.0 / 0
a = [1.0, 2, inf, 4,2]
plot, a
print, finite(a)
1 1 0 1 1
```

Just something is possible it does not make it automatically a great solution.

Reimar

```
>
> Reimar Bauer wrote:
>> Sometimes I wish people would use a defined missing value instead on
>> NaN. NaN is only defined for float and double.
>> If a NaN value is in you data everything can become difficult.
>>
>> IDL> a=[!values.f_nan,0,3,5]
>> IDL> print,max(a)
          NaN
>>
>> IDL> print,min(a)
          NaN
>> IDL> if a[0] gt 1 then print, 'yes' else print, 'no'
>> IDL> if a[0] It 1 then print, 'yes' else print, 'no'
>> no
>> IDL> if a[0] eq 1 then print, 'yes' else print, 'no'
```

```
>> no
>>
>> if you have read until here you may wonder about this
>> IDL> if !values.f_nan eq !values.f_nan then print, 'yes' else print, 'no'
>> no
>>
   Idl says "no"!!
>>
>>
>> For functions we can easily set a key so that NaN numbers can be handled
>> differently but if the default is to search for NaN a lot of other
   places needs a lot of changes.
>>
>> cheers
>>
>> Reimar
>>
>>
>> Kenneth P. Bowman schrieb:
>>> In article <MPG.238b3491ef337cc798a534@news.giganews.com>,
>>> David Fanning <news@dfanning.com> wrote:
>>>
>>>> Folks,
>>>>
>>>> I've had a couple of run-ins lately with NANs and I wonder
>>>> why routines like TOTAL and MEAN don't have the NAN keyword
>>>> set to 1 by default. Why does the user have to set it?
>>>>
>>>> I understand the argument that the NAN capability was
>>> added as an afterthought (or more likely when someone
>>> standardized the NAN bit pattern), and so the functionality
>>> was added as an optional addition that enhanced the function
>>>> rather than changed it. But really...is there a reason
>>>> why it is not the default now?
>>>>
>>> One could argue, I suppose, that having a program stumble
>>> over a NAN alerts you to its presence in your data. That
>>> is useful, certainly. But, typically, once I add a NAN
>>> keyword to my code, I don't know (nor do I or care) if the
>>> argument has NANs. Is this lazy programming on my part?
>>>>
>>>> I am just wondering whether not setting the default value
>>> of the NAN keyword to 1 on routines like TOTAL, MEAN,
>>>> et. al is the functional equivalent of not setting the
>>> default values of the COLOR and BITS_PER_PIXEL keywords
>>>> to the PostScript device to something useful by default.
>>>> That is, an act of negligence on the part of the
>>>> manufacturer.
>>>>
```

```
>>>> What say you?
>>>>
>>>> Cheers,
>>>>
>>>> David
>>> HI David,
>>>
>>> I think they chose correctly and erred on the side of safety.
>>>
>>> If I know there are Nans in my data, I'll take care of it.
>>>
>>> If there are Nans in the data that I don't expect, I don't want to
>>> have to set a keyword somewhere to find that out. That is, I don't
>>> want IDL to automatically skip those Nans.
>>>
>>> OTOH, I still find this to be frustrating and dangerous
>>> IDL> PRINT, TOTAL(REPLICATE(!VALUES.F_NAN, 5), /NAN)
        0.00000
>>>
>>>
>>> There are no valid numbers in the input vector, but TOTAL
>>> returns a valid FLOAT. This makes the NAN keyword useless
>>> in many situations.
>>>
>>> Ken
```