
Subject: Anyway to avoid this last for loop
Posted by [hldevil](#) on Thu, 08 Jan 2009 09:59:41 GMT
[View Forum Message](#) <> [Reply to Message](#)

Hi Everybody,

after having worked my way through dfannings and jdsmiths histogram tips I still haven't found a way to avoid one last (and time consuming) FOR-loop. Maybe someone has an idea.

I have two lists (Millions of entries): one containing detector hit-times, one containing anticoincidence hit-times. Only those detector hits which do not have a AC event at the same time are supposed to be kept.

I used a histogram approach:

;AClength is how many frames are thrown out after one AC Hit ->
multiple entries can fall into one bin

```
detHist=histogram(data,REVERSE_INDICES=ri, /L64, binSize=AClength)
acHist=histogram(ACdeletes, /L64, binSize=AClength)
```

```
;renormalize to one
dl=where(detHist GT 1, cntD)
al=where(acHist GT 1, cntA)
IF cntD NE 0 THEN detHist[dl]=1
IF cntA NE 0 THEN acHist[al]=1
```

```
;subtract the two histograms. All detector frames which have
corresponding AC frame should now have value 0, if AC frame exists but
not detector frame then value is -1. If only detector frame exists
(the ones we want) value stays 1!!!
diffHist=detHist-acHist
```

```
;keep the ones with one
keep=where(diffHist EQ 1, cnt)
```

;And now my problem. I need the indices of the keep-frames but there can be more than one in a bin so I'm stuck with this loop:

```
FOR k=0L, cnt-1 DO BEGIN
    keepIndices=[keepIndices,ri[ri[keep[k]]:ri[keep[k]+1]-1]]
ENDFOR
```

Is there any way I can avoid this, especially because it scales with the number of hits which are kept.

Best Regards,

Steffen
