
Subject: Re: creating dynamic array
Posted by [David Fanning](#) on Wed, 07 Jan 2009 13:32:36 GMT
[View Forum Message](#) <> [Reply to Message](#)

Bennett writes:

```
> On Jan 6, 5:55=A0pm, David Fanning <n...@dfanning.com> wrote:
>> nakisa writes:
>>> I have a file of data of
>>> =A0x,y,L .
>>
>>> I need to compare of L with a fix value and plot (x,y) with less " L "
>>> with one color and the other (x,y ) with other color.
>>
>>> The problem is I need to compare =A0L ,then store the x and y s in new
>>> variable , for example new_1 and new2 ,then plot them.
>>
>>> Fro this plot, I think the only way is to store data in array. but I
>>> need dynamic array and I don't know how can I create dynamic array ?
>>
>> I'm guessing the WHERE function might be your friend.
>>
>> IDL> ? where
>>
>> Cheers,
>>
>> David
>
> And pointers could be useful for dynamic arrays.
```

Except this didn't sound like much of a dynamic array problem. :-(

Cheers,

David

--

David Fanning, Ph.D.
Fanning Software Consulting, Inc.
Coyote's Guide to IDL Programming: <http://www.dfanning.com/>
Sepore ma de ni thui. ("Perhaps thou speakest truth.")
