

---

Subject: Re: Update text widget  
Posted by [titan](#) on Thu, 19 Feb 2009 18:10:23 GMT  
[View Forum Message](#) <> [Reply to Message](#)

---

Hi J.H.,  
excuse me if I was too cryptic in my previous message.

>  
> 1) I'm not sure where your events are supposed to be coming from.  
> Since all of your text widgets are unsensitive they can't produce any  
> events and you have no buttons to click, slider to mover , etc.  
What I want to do is to change the status of the text widget I create  
from SENSITIVE = 0 to SENSITIVE=1 after a series of calculus is  
performed. For example consider a simple for cycle

```
FOR i = 0, 5000 DO BEGIN  
Print, i  
ENDFOR
```

once this cycle is finished I would like to communicate it to the  
event handler and change the status of the corresponding row making it  
sensitive

I hope now I was clearer than before

> 2) In the event handler, you are using variables that you defined in  
> the my\_widget\_text but have not passed in any way to the event  
> handler. The event handler doesn't know what text\_1 or text\_1\_msg  
> are. One common way to handle this type of issue is to create a  
> pointer to a structure that contains all of the information that your  
> event handler might need. Then set the uvalue of you top level base  
> to that pointer. I prefer to do this kind of stuff as an object.  
> This allows you to define the widgets as member data and have access  
> to all of them throughout the event handler.

unfortunately I don't know much about pointer that's why I was trying  
to use the keyword GET\_UVALUE but now I understand that it is  
incorrect :o(