

---

Subject: Re: match\_2d

Posted by [JDS](#) on Wed, 29 Apr 2009 20:29:43 GMT

[View Forum Message](#) <> [Reply to Message](#)

---

On Apr 28, 10:44 pm, Jeremy Bailin <astroco...@gmail.com> wrote:

> On Apr 27, 3:06 pm, JDS <jdtsmith.nos...@yahoo.com> wrote:

>

>>> I'm pretty sure there's a HIST\_ND-based algorithm of doing this

>>> similar to MATCH\_2D but taking spherical trig into account, but I

>>> don't have the patience to figure it out.

>

>> That would be challenging for the whole sphere, since histogram can

>> only evaluate monotonic coordinate fields. You can always first remap

>> your coordinates using some projection which puts the ill-behaved

>> parts (nominally, the poles) far away, and preserves distance

>> locally. For example, if you have a small field (a degree or so) near

>> the pole, this would be a nice way of solving the converging longitude

>> lines issues. But generally? Sounds tough.

>

>> JD

>

> How about if it was done in 3D? Instead of 2D angular coordinates, use

> the 3D coordinates of the relevant points on the surface of a unit

> sphere, and then use HIST\_ND to determine which 3D bin the points are

> in and build the algorithm analogously to MATCH\_2D?

>

> The main problem I see is that, for small bin sizes (ie. small desired

> angular separations), there's a lot of wasted memory storing the

> histogram in locations that don't lie on the surface of the sphere and

> therefore are necessarily zero. But maybe there's a way of enumerating

> the bins that do contain part of the surface - if so, then you could

> use that enumeration to map the 3D positions into a simple number that

> you can run HISTOGRAM on.

I thought of that and rejected it for the reason you mention. The vast majority of memory would be devoted to empty volume, and as the resolution grew, the fraction of wasted memory would grow as well. The mapping you describe to do away with the empty space is equivalent to spherical projection, for which there is no unique mapping for the whole sphere. One possibility would be to project iteratively, forming low distortion projections over the sphere to push the poles off out of the way, matching against a subset of the data, rotate the projection, repeat. Some heuristic for deciding which projection, how large, and where to center it, would be needed.

At some point, it would become simpler to use pattern matching via Delauney triangulation or other patterns formed from the target list.

JD

---