
Subject: Re: How to get windows id or title by clicking on it
Posted by [David Fanning](#) on Fri, 19 Jun 2009 04:12:33 GMT
[View Forum Message](#) <> [Reply to Message](#)

Jeanphi62 writes:

```
> With
>
>
> tlb = widget_base(title="mywindow", MBAR=mbar, /col, $
>                   event_pro='test_function')
>
>
>
> and
>
>
>
>
> pro test_function, event
> print, "hello"
> end
>
>
>
> There is no "hello" printed when I click on the widget_base...
```

Well, if this is your code, you don't have any events turned on for the base widget! ;-)

This code will generate events.

```
pro test_tlb_events, event
thisEvent = tag_names(event, /structure_name)
Print, thisEvent
end

pro test
tlb = widget_base(title="mywindow", MBAR=mbar, /col, $
    /tlb_size_events, $
    /tlb_move_events, $
    /tlb_kill_request_events)
draw = widget_draw(tlb, xsize=400, ys=400)
widget_control, tlb, /realize
xmanager, 'test', tlb, /no_block, event_handler='test_tlb_events'
end
```

Cheers,

David

--

David Fanning, Ph.D.
Fanning Software Consulting, Inc.
Coyote's Guide to IDL Programming: <http://www.dfanning.com/>
Sepore ma de ni thui. ("Perhaps thou speakest truth.")
