
Subject: Re: How to get windows id or title by clicking on it
Posted by [David Fanning](#) on Fri, 19 Jun 2009 02:53:12 GMT
[View Forum Message](#) <> [Reply to Message](#)

Jeanphi62 writes:

```
> I have to link the event tlb_kill_request_events with the function
> close_window.pro and the event kbrd_focus_events with the function
> test_window.pro (this function gives me the number of the window) so I
> tried :
>
> tlb = widget_base(title="mywindow", MBAR=mbar, /col, $
>           /tlb_kill_request_events, event_pro=close_window, $
>           /kbrd_focus_events, event_pro='test_window')
>
> but the software crashes.
```

No, no. You can only have one event handler for a widget.
When you get into that event handler, you can decide if the
event is a kill request or a keyboard focus event:

```
thisEventName = Tag_Names(event)
CASE thisEventName OF
```

```
'WIDGET_KILL_REQUEST': BEGIN....
```

```
    'WIDGET_KBRD_FOCUS': BEGIN...
```

```
    ELSE: Print, 'Yikes. Do not have a clue!!'
```

```
ENDCASE
```

Cheers,

David

--

David Fanning, Ph.D.
Fanning Software Consulting, Inc.
Coyote's Guide to IDL Programming: <http://www.dfanning.com/>
Sepore ma de ni thui. ("Perhaps thou speakest truth.")
