

---

Subject: Re: unix/idl question

Posted by [oxfordenergyservices](#) on Mon, 22 Jun 2009 12:35:56 GMT

[View Forum Message](#) <> [Reply to Message](#)

---

On 22 June, 12:55, FÖLDY Lajos <fo...@rmki.kfki.hu> wrote:

> On Mon, 22 Jun 2009, a wrote:

>> Hi

>

>> I am having a problem that i want to delete many files with the 'raw'

>> extension in folder temp

>

>> in unix

>

>> cd temp

>> rm \*raw

>> /bin/rm: Argument list too long.

>

>> ok, so

>

>> cd temp

>> ls -l | grep raw | awk '{print \$9}' | xargs rm

>

>> works ok

>

>> but I have to be in the directory to do it

>

>> I want to do the same from idl and not being in the temp directory

>

>> ie

>

>> spawn,'cd temp'

>> spawn,'ls -l | grep raw | awk '{print \$9}' | xargs rm '

>

>> but the first spawn does not leave me in the temp directory

>

>> any ideas?

>

>> Thanks

>

>> Russ

>

> find /tmp/ -name '\*raw' | xargs rm

>

> or (for files with whitespace in the names):

>

> find /tmp/ -name '\*raw' -print0 | xargs -0 rm

>

> regards,

> lajos

many thanks! works a treat

Russ

---