Subject: Re: data criteria

Posted by Jean H. on Mon, 24 Aug 2009 15:14:54 GMT

View Forum Message <> Reply to Message

```
anil wrote:
> Hi all,
> I do not have much information about programming or algorithms
> (actually IDL is my first programming language), so my question may
> rather be simple but i could not figure it out, so here we go:
> ......
> So I want to take the lines from the first line up to 12.654200(since
> the difference is more than 0.3)
> What i have done so far is:
>
> pro a
> ;window, 0, retain=2
>
> file_array=file_search('/home/....../0587', '0587.*.txt',
> count=num file)
> for i=0,num_file-1 do begin
> file=file_array(i)
>
  nrows = File_Lines(file)
>
  data=fltarr(5,nrows)
>
> OpenR, lun, file, /GET_LUN
> ReadF, lun, data
> Free Lun, lun
>
> p = data(0,*)
> t=data(1,*)
> s=data(2,*)
> q=data(3,*)
> d=data(4,*)
> close,lun
> free_lun, lun
>
> 1st try
> ;for k=1,nrows-2 do begin k=k+1
> ;ml=where((d(k+1)-d(k)) qt 0.3,ss)
  :endfor
>
>
> 2nd try
> :k=1
> ;repeat begin ml=(d(k)-d(k-1))
>; k=k+1
> ;endrep until (ml gt 0.3)
```

```
> ;print,d(0:k)
```

- > free_lun,lun
- > endfor

- > close,/All
- > end

- > Neither of them work ! I used an if-then-else statement too but could
- > not solve my problem.
- > I would really appreciate any help. Thanks in advance,
- > ANIL

Hi Anil,

the problem with your code is that you are not using not saving ML... so you erase it in each loop.

You could do it this way:

```
toKeepIDX = where(d - shift(d,-1) ge 0.3)
goodData = data[*,toKeepIDX]
and/or: goodA = a[toKeepIDX] goodB = b[toKeeIDX] etc
```

In the first line, you compare each entry with its previous one and you select ALL entries according to your criterion. Next, you extract the data itself.

This will bring a problem for the first entry of course. Also, keep in mind the case where you don't have the .3 of different between 3 consecutive values (1, 1.01, 1.02, 1.03 etc)

Jean