
Subject: Re: Plot single data points in IMAP
Posted by [penteado](#) on Thu, 05 Nov 2009 16:55:57 GMT
[View Forum Message](#) <> [Reply to Message](#)

On Nov 5, 11:35 am, "Karlo Janos" <groups.20.beam...@spamgourmet.com> wrote:

> Dear all,
>
> I am wondering if it is possible to plot single data points in a map
> set produced with IMAP.
> In the help document I only found examples for overplotting IMAP with
> images or vector fields with regularly gridded.
>
> In direct graphics mode I would use "MAP_SET, ..." and then plot single
> data points by "PLOTS, lons, lats, ...". In this case "lons" and "lats"
> can be arbitrary coordinates from the intervals [-180; 180] and
> [-90;90], respectively.
> Is there any way to get a similar result with IMAP?
>
> Thanks in advance,
>
> Karlo

I think you need to use iplot to overplot on the imap, with your lats and lons converted to cartesian coordinates. As an example:

```
lats=[60.,30.,0.,-60.,-45.,60.]  
lons=[-60.,0.,120.,30.,-60.,-60.]  
imap,map_projection='sinusoidal'  
mp=map_proj_init('sinusoidal')  
xy=map_proj_forward(lons,lats,map_structure=mp)  
iplot,xy,/over,color=[255,0,0]
```
