Subject: Re: Could you explain why this happen? Posted by bryan.s.hong on Wed, 28 Apr 2010 17:54:40 GMT

View Forum Message <> Reply to Message

```
> Bryan writes:
>> This may be a stupid question, but I really want to know why.
>> Please, see below and explain. Thanks.
>> IDL> print, 132*30
      3960
>> IDL> print, 132*30*10
    -25936
>> IDL> print, 132*300
   -25936
>> IDL> data1 = 132
>> IDL> data2 = 300
>> IDL> data3 = data1*data2
>> IDL> print, data3
   -25936
> Here is a clue. These are the same IDL commands in my IDL
  session:
>
  IDL> print, 132*30
       3960
>
  IDL> print, 132*30*10
      39600
 IDL> print, 132*300
      39600
> IDL> data1 = 132
> IDL> data2 = 300
> IDL> data3 = data1*data2
> IDL> print, data3
      39600
>
  Probably the only difference between your IDL session and mine
  is that I have this command in my IDL startup file:
>
    compile_opt defint32
>
  Why would that matter?
>
 Cheers,
>
 David
```

- > David Fanning, Ph.D.
- > Fanning Software Consulting, Inc.
- > Coyote's Guide to IDL Programming:http://www.dfanning.com/
- > Sepore ma de ni thui. ("Perhaps thou speakest truth.")

Thank you for your kind response. Then, could you let me know how to set the IDL start-up file like you?

Thanks.		
Bryan		