
Subject: Re: ESRI shape file

Posted by [Klemen](#) on Sat, 28 Aug 2010 11:31:17 GMT

[View Forum Message](#) <> [Reply to Message](#)

There is an example of creating a point shape file in Help as Max said (see below). Creating a polygon is slightly more difficult; if you need such an example let me know.

Cheers, Klemen

PRO ex_shapefile_newfile

;Create the new shapefile and define the entity type to Point
mynewshape=OBJ_NEW('IDLffShape', FILEPATH('cities.shp', \$
SUBDIR=['examples', 'data']), /UPDATE, ENTITY_TYPE=1)

;Set the attribute definitions for the new Shapefile
mynewshape->AddAttribute, 'CITY_NAME', 7, 25, \$
PRECISION=0
mynewshape->AddAttribute, 'STAT_NAME', 7, 25, \$
PRECISION=0

;Create structure for new entity
entNew = {IDL_SHAPE_ENTITY}

; Define the values for the new entity
entNew.SHAPE_TYPE = 1
entNew.BOUNDS[0] = -104.87270
entNew.BOUNDS[1] = 39.768040
entNew.BOUNDS[2] = 0.00000000
entNew.BOUNDS[3] = 0.00000000
entNew.BOUNDS[4] = -104.87270
entNew.BOUNDS[5] = 39.768040
entNew.BOUNDS[6] = 0.00000000
entNew.BOUNDS[7] = 0.00000000
entNew.N_VERTICES = 1 ; take out of example, need as workaround

;Create structure for new attributes
attrNew = mynewshape ->GetAttributes(/ATTRIBUTE_STRUCTURE)

;Define the values for the new attributes
attrNew.ATTRIBUTE_0 = 'Denver'
attrNew.ATTRIBUTE_1 = 'Colorado'

;Add the new entity to new shapefile
mynewshape -> PutEntity, entNew

;Note that because this is a new shapefile, the index of

```
;the new entity is zero.  
entity_index=0  
  
;Add the Colorado attributes to new shapefile.  
mynewshape -> SetAttributes, entity_index, attrNew  
  
;Close the shapefile  
OBJ_DESTROY, mynewshape  
  
END
```
