
Subject: Re: Blanking all 5x5 windows with less than X 'on' pixels in them
Posted by [rogass](#) on Fri, 21 Jan 2011 14:23:11 GMT
[View Forum Message](#) <> [Reply to Message](#)

On 21 Jan., 10:02, Robin Wilson <ro...@rtwilson.com> wrote:

> Hi Chris,
>
> That's great. Yes, your description is correct - that's exactly what I
> want to do.
>
> Cheers,
>
> Robin
>
>
>
>
>
>
>
>
>> Hi Robin,
>> i have such a vectorised function. Please give more details. Do you
>> want to clean all pixels including the center pixel in a moving
>> window, if the center pixel is below a threshold?
>
>> Cheers
>
>> CR

; conv is the 2D convolution result

```
IDL> conv=randomn(seed,100,100)
IDL> x=mean(conv);threshold
IDL> wx=3 & wy=3;moving window size
IDL> sz=size(conv,/dimensions)
IDL> ind=cr_get_window(sz,wx,wy);get indices of moving window as index
vector of size [wx,wy,n_elements(conv)]
IDL> wh = where((conv[ind])[wx/2,wy/2,*] gt X);evaluate center pixel
due to threshold
IDL> ind[*,* ,wh]=-1;set all indices in matched windows to -1
IDL> ind2=uniq(((wi=ind[where(ind ne -1)]),sort(wi)));extract uniq
indices due to same indices in adjacent windows
IDL> conv[ind2]=0
IDL> tvscl,conv,0
IDL> tvscl,conv eq 0,1
```

```
function cr_get_window,sz,wx,wy,mode=mode,ind=ind
on_error,2
```

```

sx = long(sz[0])
sy = long(sz[1])
wx = long(n_elements(wx) gt 0 ? wx : 3)
wy = long(n_elements(wy) gt 0 ? wy : 3)
mode= keyword_set(mode) ? -1>mode<3 : 0
ind = keyword_set(ind) ? ind : 0
a = n_elements(ind) le 1 ? ulindgen(sx,sy) : ind
h = a[0:wx-1,0:wy-1] mod wx
ind = rebin(h + rebin(transpose(h[0:wx-1]*sx),wx,wy,/sample),wx,wy,
((ss=sx*sy)),/sample)+$
  rebin(reform(a[*],1,1,ss,/over),wx,wy,ss,/sample)
if n_elements(sz) eq 3 then begin
  mode=0
  ind2 = sz[2] le ss? reform(a[0:sz[2]-1],1,1,1,sz[2],/over) : $
    (ss le sz[2]? reform((a[*])[0:sz[2]-1],1,1,1,sz[2],/over) :
  ulindgen(1,1,1,sz[2]))
endif
undefine,h,a
case mode of
0 : result= n_elements(sz) lt 3? ind : rebin(ind, wx,wy,ss,sz[2],/
sample) + $
  rebin(ind2*ss,wx,wy,ss,sz[2],/sample)
1 : result= reform(ind,wx*wy,sx*sy,/over)
2 : result= ind[*]
else: result=-1
endcase
undefine, sx,sy,mode,ind
undefine, ind2
return, result
end

```

Hope it helps

Cheers

CR