## Subject: Re: getting/setting value of unknown tag of structure??? Posted by Tim Patterson on Wed, 18 Dec 1996 08:00:00 GMT

View Forum Message <> Reply to Message

Well, it seems to me you're creating trouble for yourself by allowing the user to create structures like this (and the IDL code you wrote doesn't quite work as it stands on my system), but...

```
text = 'mystruct.'+thetagis+' = "THE NEW VALUE""
test = execute(text)
... should work
Tim
Hendrik Roepcke wrote:
> Hello,
> imagine the little program:
> pro problem
  read,mytagname,prompt="Enter Tagname: "
  read,myvalue,prompt="This into it: "
>
  mystruct=create_struct([mytagname, 'test'],[myvalue,myvalue])
>
 ; this is easy and works
  print, mystruct.test
>
> ; but how to get the myvalue via the first tagname?
  print, mystruct.????
>
 ; ok, i can fetch it via tag_names:
 thetagis=tag_names(mystruct)
> thetagis=thetagis(0)
 print,thetagis
>
  ; and my main problem is: how to set the unknown tag?
> mystruct.???='THE NEW VALUE'
>
> end
> OK, any help needed...
```

```
> Panther
> PS: greetings to the housekeeper of wayward inodes...
>
> --
> Panther in the Jungle __..-"``\--...._
> -BELIEVE AND DECEIVE- __.-' .-/"; `
> http://www.ang-physik _.-' _..-.' \
> .uni-kiel.de/~hendrik ((..-' (< _ ;_..__
```