
Subject: Re: How do I change time on a dataset
Posted by [Wout De Nolf](#) on Fri, 05 Aug 2011 10:08:21 GMT
[View Forum Message](#) <> [Reply to Message](#)

On Thu, 4 Aug 2011 10:33:00 -0700 (PDT), Ahmed Salahuddin
<salahuddin0812@gmail.com> wrote:

```
> Here is what I have from the file of
> hadam3p_pnw_zes_1999_1_006983552_0_1 Folder
> zezsga.pdj9dec.pnw.nc
> zezsga.pdk0jan.pnw.nc
> zezsga.pdk0feb.pnw.nc
> zezsga.pdk0mar.pnw.nc
> zezsga.pdk0apr.pnw.nc
> zezsga.pdk0may.pnw.nc
> zezsga.pdk0jun.pnw.nc
> zezsga.pdk0jul.pnw.nc
> zezsga.pdk0aug.pnw.nc
> zezsga.pdk0sep.pnw.nc
> zezsga.pdk0oct.pnw.nc
> zezsga.pdk0nov.pnw.nc

> for i=12,334 do begin ; I have 27 years starting from 1980
>   if imo gt 11 then begin
>     imo=0
>   endif
>   vararr=tavg(*,*,i) ; I calculated temp avg
>   for iarea=0,nareas-1 do begin ; I have 8 areas
>     domain=c_area(iarea)
>     inarr=vararr(*,*)
>     regcpdn_area_avg,domain,WOCmask,WOMmask,WOEmask,WOImask,CAmask,
CVmask,WUSmask,WVmask,lon,lat,inarr,outval
>     obsarr(iyear,imo,iarea)=outval
>     if finite(outval) eq 0 then stop
>   endfor
>   print,1979+iyear,imo
>   if imo eq 0 then iyear=iyear+1
>   imo=imo+1
> endfor
>
>
> Regards,
> salahud
```

As for the IDL code, I understand

1. imo: month counter [0,11] = [jan,dec]
2. iyear: year counter (iyear=0 => 1979)
3. i: loop counter = months starting from jan 1980 (i=0 => jan 1980)
4. Since i starts from 12 I suppose, from the logic of the loop that iyear=1 and imo=12
5. If you loop over 27 years (=324 months) shouldn't you do:
for i=12,335 do begin ...

Then the loop logic is beyond me. From the comment "I have 27 years starting from 1980" I would expect this to be printed:

```
1980    0    (jan 1980)
1980    1
1980    2
...
2006    9
2006   10
2006   11    (dec 2006)
```

What we get however is this (which explains the 1 year shift)

```
1980    0    (jan 1980)
1981    1    (feb 1981)
1981    2
...
2007    8
2007    9
2007   10    (oct 2007)
```

Unless 0=dec, 1=jan, ... but that doesn't make sense for obsarr(iyear,imo,iarea). So instead of this:

```
iyear=1
imo=12
for i=12,334 do begin
  if imo gt 11 then begin
    imo=0
  endif
  ...
  print,1979+iyear,imo
  if imo eq 0 then iyear=iyear+1
  imo=imo+1
endfor
```

You could do this:

```
for i=12,335 do begin
  imo=i mod 12
```

```
iyear=i/12
...
print,1979+iyear,imo
endfor
```

Also make sure that `obsarr(iyear,imo,iarea)` is correct. Since you start from jan 1980, `obsarr(iyear,*,*)` will be empty (whole of 1979).

Then back to your files:
zezsga.pdj9dec.pnw.nc
zezsga.pdk0jan.pnw.nc
zezsga.pdk0feb.pnw.nc

As for the filename-date correlation, don't you have scanning description files like zezsga.pdj9dec.ctf? 0 jan doesn't make sense... Now instead of starting from jan 1980 and spanning 27 years, these files start from dec 1999 and end at nov 2000 (by your understanding). Then you would need to do

```
for i=251,262 do begin
  imo=i mod 12
  iyear=i/12
  ...
  print,1979+iyear,imo
  if i eq 30 then break
endfor
```

However I suspect `tavg(*,*,i)` doesn't reach back to jan 1979, so my assumptions might be wrong. What is the relation between `tavg` and the data files? Anyway, you probably get the idea by now.
