
Subject: Re: Resizing a widget base

Posted by [davidf](#) on Mon, 13 Jan 1997 08:00:00 GMT

[View Forum Message](#) <> [Reply to Message](#)

Ken Stone <k.a.stone@larc.nasa.gov> writes:

- > Has anyone used the TLB_SIZE_EVENTS keyword on a call to widget_base?
- > I'm using it on NT4, and it returns ALL (a time history I think) of the
- > resize events. From the beginning of the mouse movement to the end.
- > (Which can be fun to watch the first couple of times.) All I really
- > want is the last position. Do all the Window
- > platforms return all the events? Does anyone know how to get just
- > the last event triggered?

This has nothing to do with IDL. It is a configurable item on Windows NT machines. I am sitting in front of a Macintosh with no access to a Windows platform, but as I recall you go to the "desktop" control panel (or whatever it is called in Windows NT) and turn "window drag" option off.

If someone knows the correct terminology here, I'd be happy to put the correct info on my web page for future reference.

David

David Fanning, Ph.D.
Fanning Software Consulting
2642 Bradbury Court, Fort Collins, CO 80521
Phone: 970-221-0438 Fax: 970-221-4762
E-Mail: davidf@dfanning.com
Coyote's Guide to IDL Programming: <http://www.dfanning.com>
