

---

Subject: Re: Shape to raster

Posted by [David Fanning](#) on Mon, 31 Oct 2011 14:54:01 GMT

[View Forum Message](#) <> [Reply to Message](#)

---

Fabzou writes:

- > I have an other question though. How will the IDLanROI object
- > "understand" the XY coordinates [0.5,0.5]? In my conception, these
- > coordinates correspond to the center of the first down left pixel, but
- > my first tests tend to show that this may not be the case...

Oh, my gosh! I just spent a week worrying about this in conjunction with an update of my Active Contouring software! I don't use an IDLanROI object there, because I want to do this myself and completely understand what I am doing. In \*my\* ROI, the [0.5,0.5] location would indeed be the center of the first pixel. I don't know off-hand what the IDLanROI object will do. And I have no compelling interest in looking into it this morning, either. It makes my head hurt. :-)

Cheers,

David

P.S. If you are going to test this, however, I would test with the values 0.45 and 0.55, not the value 0.5. At some point, you are going to have to do some rounding if you want image or device coordinates. The question you want to answer is how the rounding is done.

--

David Fanning, Ph.D.

Fanning Software Consulting, Inc.

Coyote's Guide to IDL Programming: <http://www.idlcoyote.com/>

Sepore ma de ni thui. ("Perhaps thou speakest truth.")

---