Subject: Re: Replicate array over columns - using transpose? Posted by Russell[1] on Thu, 22 Mar 2012 15:18:30 GMT

View Forum Message <> Reply to Message

```
On Mar 22, 8:01 am, Craig Markwardt < craig.markwa...@gmail.com> wrote:
> On Thursday, March 22, 2012 6:11:54 AM UTC-4, robintw wrote:
>> Hi all.
>
>> I've got an array, a, as follows:
>
>> IDL> print, a
        10.0000
                   35.0000
                               60.0000
                                           85.0000
                                                      110.000
>>
>
>> I want to replicate this across 4 columns to produce an array like the
>> following:
>
>> 10 10
            10
                   10
                   35
>> 35 35
            35
>> 60 60
            60
                   60
>> 85 85
            85
                   85
>> 110
            110
                   110
                         110
>> I'm using the CMREPLICATE routine to do this, and get the following:
>> IDL> print, CMREPLICATE(a, 4)
        10.0000
                   35.0000
                               60.0000
                                           85.0000
                                                      110.000
>>
        10.0000
                   35.0000
                               60.0000
                                           85.0000
                                                      110.000
>>
        10.0000
                   35.0000
                               60.0000
                                           85.0000
                                                      110,000
>>
        10.0000
                   35.0000
                               60.0000
                                           85.0000
                                                      110.000
>>
>> However, I want to replicate it in the columns as in the example above.
>> As far as I can see it there are two ways to deal with this: transpose
>> the array after I've done it (computationally expensive, as I'll be
>> doing it with far larger arrays in the real program) or transpose it
>> before running CMREPLICATE. However, if I do this I get an extra
>> dimension added:
>> IDL> help, CMREPLICATE(transpose(a), 4)
>> <Expression> FLOAT = Array[1, 5, 4]
>> Is there a way to replicate over the columns without adding this extra
>> dimension? I'm sure I'm missing something simple here.
  I'm the CM in CMreplicate, but I wouldn't use CMreplicate. I use this instead.
>
  print, [1,1,1,1,1] # a
>
  Usually I'm matching up X and Y labels to a 2D grid, so I do this,
```

```
> XX = (X*0 + 1) # Y
> YY = X # (Y*0 + 1)
```

> Now XX and YY are 2D arrays with X running along one axis and Y running along the other axis. It looks crazy, but it works.

> Craig

Ha! I should have read on. I didn't see someone posted this answer.

Sorry for the repetition, Russell