
Subject: Re: Shut down X connection?

Posted by [Lajos Foldy](#) on Thu, 24 May 2012 11:08:17 GMT

[View Forum Message](#) <> [Reply to Message](#)

On Wednesday, May 23, 2012 10:08:51 PM UTC+2, Mark Fardal wrote:

> Hi,
>
> I'd like to know if it's possible to terminate IDL's connection to the
> X server, without terminating IDL. There has been some discussion in
> the past of how to avoid starting up an X server connection in IDL.
> This is slightly different: I want to start up the connection, shut it
> down, and start it up again. Merely changing the display device with
> set_plot, 'null' is not sufficient. If this is possible, it would
> enable moving the X display freely from one client to another, with
> the IDL session running on a server inside a "screen" session.
> Which would be nice.
>
> thanks,
> Mark

I think the X connection can not be closed. But you can run IDL in a VNC session. We were discussing it two years ago, I copy-paste my old advice:

The graphical counterpart of screen is Xvnc (vncserver). I use it with openSUSE 11.2, but I think other distros are similar:

- login to the remote host
- vncserver
 this prints something like:
 ...
 New 'X' desktop is remote:1
 ...- logout

On your local machine:

- vncviewer remote:1
- open a terminal, start your job, ...

After exiting vncviewer, you can turn off your local machine.

regards,
Lajos
