
Subject: Re: PLOT() function...which WINDOW() to plot to...?
Posted by [Paul Van Delst\[1\]](#) on Wed, 12 Sep 2012 15:58:06 GMT
[View Forum Message](#) <> [Reply to Message](#)

Hello,

On 09/12/12 11:07, David Fanning wrote:

> Paul van Delst writes:

>

>> I want to create a window, and have everything plot in that window (be
>> it onscreen or in buffer) regardless of what other graphics windows I
>> have onscreen that I happen to be looking at and click on.

>>

>> I presume there is some magical combination of keywords that will do that?

>

> I think you have to write your loop like this, using
> the SetCurrent method on the window you want to draw
> into:

>

> w.SetCurrent

> index++

> pn = PLOT(\$

[snip]

> CURRENT = 1)

Yeah, I did look at that method (and implemented it as you say) but it does not solve the basic problem.

If I click on a different window in that infinitesimal amount of time between the execution of

 w.SetCurrent

and

 pn = PLOT(...)

the same problem crops up since "w" is no longer the current window.

It's typical that, while plot#n is being written to screen, I'm looking at plot#(n-1). As soon as I click on that window and give it focus, everything goes pear-shaped. You're effectively forced to do non-IDL-y stuff while the program is (slowly) plotting all the FG graphics.

Additionally, it adds the burden of having to put a "w.SetCurrent" before every single FG call! And that *still* may not be efficacious depending on how "click-y" one is with existing windows.

It seems to be such a gaping hole in the basic design of these graphics features that I am sure I am still missing something.

- With DG clicking on windows was a completely separate operation from

setting the current graphics window in a program via WSET.

- With FG, the two operations are intertwined. Clicking on *ANY* graphics window has exactly the same effect as executing the SetCurrent method... even if the program is running, and even if the program has been directed to send all graphics to a buffer rather than onscreen.

Unless there is something in the documentation that I'm missing (or just misunderstanding), I regard this as a fundamental flaw: there is no way for a programmer to guarantee the code will run the way it was intended (i.e. *always* plot to *this* window).

Anyhoo... I guess I'll bring the donuts to the next IDL support group meeting...

cheers,

paulv

p.s. Argh!
