Subject: Re: Simple question in IDL, looking for solution, thank you Posted by Heinz Stege on Tue, 23 Oct 2012 18:07:48 GMT

View Forum Message <> Reply to Message

On Mon, 22 Oct 2012 14:10:18 -0400, Jeremy Bailin wrote:

```
> On 10/22/12 7:55 AM, Heinz Stege wrote:
>> Hi Danxia,
>>
>> you didn't ask for a solution without a loop. So here is my simple
>> answer:
>>
>> arr=[5,2,3,1,8,3,1,2,3]
>> bcg=[1,2,3,2,1,4,2,3,5]
>> sum=intarr(max(arr)+1)
>> for i=0,n_elements(bcg)-1 do sum[arr[i]]+=bcg[i]
>> print,sum[1:*]
>>
>> Cheers, Heinz
>>
> And of course, if you need a very efficient implementation of this (i.e.
> if your arrays have millions of elements), then read the "chunk
> indexing" section of JD's HISTOGRAM tutorial
> http://www.idlcoyote.com/tips/histogram_tutorial.html (you HAVE read
> JD's HISTOGRAM tutorial, right???)
> -Jeremy.
```

Hi Jeremy,

I suppose you mean something like the following:

```
h=histogram(total(bcg,/cumulative,/integer)-1,/binsize,min=0,reverse_indices=ri)
i=ri[0:n elements(h)-1]-ri[0]
print,histogram(arr[i],min=1)
```

The histogram methods in general are very smart. The above code is significantly faster than my, which contains the loop. However, from my point of view, this is not a good solution.

In case of very many elements within arr (and bcg) and/or big numbers within bcg the reverse indices array ri gets very large. The size of ri is always greater than total(bcg). IDL may run out of memory.

So I would say, the loop may compete with the reverse indices.

When I wrote "simple answer", I had in mind that there must be another solution. One without a loop. It is more the "IDL-style". But it is a little bit more complex:

```
ii=sort(arr)
sarr=arr[ii]
tot=total(bcg[ii],/cumulative,/integer)
;
ii=where(sarr ne shift(sarr,-1),count)
if count eq 0 then ii=[n_elements(sarr)-1]
tot=tot[ii]
if count ge 2 then tot[1:*]-=tot
;
sum=lonarr(sarr[n_elements(sarr)-1]+1)
sum[sarr[ii]]=tot
;
print,sum[1:*]
```

This code has a moderate memory consumption and seems to be a true alternative to both, the loop-method and the reverse-indices-method.

A word to the developers of IDL: What about a WEIGHT keyword in the histogram function?

print,histogram(arr,weight=bcg,/integer,min=1)

This would be nice. By the way, when I type the line above, IDL (Version 8.0.1) says:

% Keyword INTEGER not allowed in call to: HISTOGRAM

% Error occurred at: \$MAIN\$ % Execution halted at: \$MAIN\$

No integer keyword allowed in the histogram function? Strange! ;-)

Cheers, Heinz