

---

Subject: Re: A QuerrVizier error?

Posted by [Celeritas](#) on Mon, 25 Mar 2013 07:29:16 GMT

[View Forum Message](#) <> [Reply to Message](#)

---

thank you so much. Works perfect.

\Mads

On Monday, March 25, 2013 4:20:52 AM UTC+1, wlandsman wrote:

> The problem is that there are actually two catalogs - a catalog of open cluster data (cocd) and a notes catalog. queryvizier should be able to figure out how to separate the two catalogs, but meanwhile you can work around this by specifically searching the cocd data.

```
>
>
>
> OC1 = queryvizier('J/A+A/438/1163/cocd','None',/allcolumns,/verbose)
```

```
>
>
>
>
> --Wayne
```

> On Sunday, March 24, 2013 11:56:42 AM UTC-4, Celeritas wrote:

```
>
>
>
>>
>
>> OC1 = queryvizier('J/A+A/438/1163','None',/allcolumns)
```

```
>
>>
>
>>
>
>>
>
>>
>
>>
>
>>
>
>>
>
>>
>
>>
>
>>
>
>>
>
>>
>
>>
>
>>
>
>>
>
>>
>
>>
>
>>
```

>> IDL responds with

>> %Type conversion error: Unable to convert given STRING to Long.

```
>
>>
```

```
>  
>> % Detected at: QUERYVIZIER      339  
C:\Users\MS\Desktop\IDL_functions\vizier\QueryVizier.pro  
>  
>>  
>  
>> % Conflicting or duplicate structure tag definition: RECNO_2.  
>  
>>  
>  
>>  
>  
>>  
>  
>>  
>  
>>  
>  
>> Line 339 is within the following loop, see arrow for precise mark.  
>  
>>  
>  
>>  
>  
>>  
>  
>>  
>  
>>  
>  
>> ; Find positions of tab characters  
>  
>>  
>  
>>  
>  
>> t = t[i0:iend-1]  
>  
>>  
>  
>>  
>  
>>  
>  
>>  
>  
>> for j=0,Ntag-1 do begin  
>  
>>  
>  
>>     x = strtrim( gettok(t,string(9b),/exact ),2)  
>  
>>  
>  
>>     dtype = size(info[0].(j),/type)  
>  
>>  
>  
>>     if dtype NE 7 then begin  
>
```



```
>>  
>  
>> \Mads
```

---