
Subject: Re: regression with 95% confidence interval
Posted by [Kenneth Bowman](#) on Mon, 22 Jul 2013 15:57:47 GMT
[View Forum Message](#) <> [Reply to Message](#)

On 2013-07-22 15:11:51 +0000, Fabien said:

> On 07/22/2013 03:35 PM, Kenneth Bowman wrote:
> I e-mailed you a routine that will compute confidence limits on the
>> slope and intercept.
>
> I am interested in your method too ;-). Could you mail it to me too?

It is a short routine, so I have pasted it below.

The function computes a linear regression and confidence limits on the slope and intercept following the examples in Tamhane and Dunlop, which is an introductory graduate-level statistics book. As always, the robustness of the confidence limits depends on whether the underlying statistics of the process in question satisfy the assumptions that are made in deriving the confidence limits. In this case the predictor (x) is assumed to be known with no error, and the error in the predictand (y) is assumed normal. It wouldn't hurt to look at Tamhane and Dunlop, for more details.

Cheers, Ken

```
FUNCTION REGRESSION_STATISTICS_KPB, x, y, $
```

```
  CI    = ci,  $
```

```
  DOUBLE = double, $
```

```
  VERBOSE = verbose
```

```
;+
```

```
; Name:
```

```
;   REGRESSION_STATISTICS_KPB
```

```
; Purpose:
```

```
;   This program computes the regression coefficients a and b and  
their confidence limits
```

```
;   for simple bivariate linear regression
```

```
;
```

```
;    $y = a + b \cdot x + \text{eps}$ 
```

```
;
```

```
;   The calculations follow the exposition in Chap. 10 of Tamhane and  
Dunlop (2000).
```

```
; Calling sequence:
```

```
;   stats = REGRESSION_STATISTICS_KPB(x, y[, ci])
```

```
; Inputs:
```

```

;   x       : Values of the independent variables.
;   y       : Values of the independent variables.
; Output:
;   stats   : Data structure containing various statistics and
confidence limits.
; Keywords:
;   CI      : Optional confidence limit (%). If not set, a default
value of 95% is used.
;   VERBOSE : If set, print the statistics and confidence intervals.
; Author and history:
;   Kenneth P. Bowman. 2007-11-01.
;-

IF (N_PARAMS() NE 2) THEN MESSAGE, 'Incorrect number of arguments.'
;Check number of arguments

IF (N_ELEMENTS(ci) EQ 0) THEN ci = 95.0D0
;Default confidence limit to calculate

n = N_ELEMENTS(x)
;Number of data points
IF (N_ELEMENTS(y) NE n) THEN $
;Check array sizes
MESSAGE, 'The number of x and y values must be equal.'

b = (REGRESS(x, y, CONST = a, YFIT = yfit, FTEST = f_stat, $
;Compute regression and extract value of b
CORRELATION = r, CHISQ = chisq, DOUBLE = double))[0]

s   = SQRT(TOTAL((yfit - y)^2)/(n-2))
;Standard deviation of the residuals
x_mean = MEAN(x)
;Mean of the x values
y_mean = MEAN(y)
;Mean of the y values
S_xx = TOTAL((x - x_mean)^2)
;Sum of the squared deviations of x from the mean
S_yy = TOTAL((y - y_mean)^2)
;Sum of the squared deviations of y from the mean
S_xy = TOTAL((x - x_mean)*(y - y_mean))
;Sum of the products of the deviations of x and y from their
means
SE_a = s*SQRT(TOTAL(x^2)/(n*S_xx))
;Standard error of a
SE_b = s/SQRT(S_xx)
;Standard error of b
alpha = (1.0D0 - 0.01D0*ci)/2.0D0
;Level for t-test

```

```

t_stat = T_CVF(alpha, n-2)
;Compute t-statistic

IF KEYWORD_SET(verbose) THEN BEGIN
  PRINT, 'Intercept (a)      : ', a
  PRINT, 'Slope (b)         : ', b
  PRINT, 'Correlation coefficient r : ', r
  PRINT, 'r^2                : ', r^2
  PRINT, 'F-statistic        : ', f_stat
  PRINT, 'Chi-square statistic : ', chisq
  PRINT, 'n                  : ', n
  PRINT, 'Mean of x          : ', x_mean
  PRINT, 'Mean of y          : ', y_mean
  PRINT, 'S.D. of residuals   : ', s
  PRINT, 'S_xx               : ', S_xx
  PRINT, 'S_yy               : ', S_yy
  PRINT, 'S_xy               : ', S_xy
  PRINT, 'S.E. of a           : ', SE_a
  PRINT, 'S.E. of b           : ', SE_b
  PRINT, 'Confidence limit    : ', ci, '%'
  PRINT, 'Level for t-test    : ', alpha
  PRINT, 't-statistic         : ', t_stat
  PRINT, 'Confidence interval for a : ', a, '+/-',
STRTRIM(t_stat*SE_a, 2), ' [', a - t_stat*SE_a, ', ', a + t_stat*SE_a,
']'
  PRINT, 'Confidence interval for b : ', b, '+/-',
STRTRIM(t_stat*SE_b, 2), ' [', b - t_stat*SE_b, ', ', b + t_stat*SE_b,
']'
ENDIF

RETURN, {a      : a,      $
;Y-intercept
      b      : b,      $
;Slope
      r      : r,      $
;Correlation coefficient r
      yfit    : yfit,    $
;Fitted values at x
      f_stat   : f_stat,  $
;F-statistic
      chisq    : chisq,   $
;Chi-squared statistic
      n       : n,       $
;Number of points
      x_mean   : x_mean,  $
;Mean of the x values
      y_mean   : y_mean,  $
;Mean of the y values

```

```

      s      : s,      $
;Standard deviation of the residuals
      S_xx    : S_xx,    $
;Sum of the squared deviations of x from its mean
      S_yy    : S_yy,    $
;Sum of the squared deviations of x from its mean
      S_xy    : S_xy,    $
;Sum of the products of the deviations of x and y from their means
      SE_a    : SE_a,    $
;Standard error of a
      SE_b    : SE_b,    $
;Standard error of b
      ci      : ci,      $
;Requested confidence interval (%)
      alpha   : alpha,   $
;Level for t-test
      t_stat  : t_stat,  $
;t-statistic value
      ci_a    : t_stat*SE_a, $
;Confidence interval for a is (a +/- ci_a)
      ci_b    : t_stat*SE_b }
;Confidence interval for b is (b +/- ci_b)

```

END
