
Subject: Issue using map_set and !p.multi in combination with polyfill to colour window backgrounds

Posted by [Andy Sayer](#) on Fri, 23 Aug 2013 14:00:03 GMT

[View Forum Message](#) <> [Reply to Message](#)

Hi all,

I'm having a slight issue with a combination of polyfill, map_set, and !P.multi...

Basically, I would like to set up multiple maps per page with the option of having a different colour background for each individual map (which will normally be black or white). I know I can change background colours with Coyote Graphics, but I only want to colour a portion of the window, not the whole thing, if I am drawing multiple plots to the window. So I have been writing some test code to check this out. This is what I have so far:

```
!P.multi=[0,7,5]
loadct,2
```

```
window,0,xsize=1500,ysize=800
for i=0,!p.multi[1]*!p.multi[2]-1 do begin
```

```
    ; Get coordinates of this plot subregion for polyfill.
    ; Can't colour the whole window as it won't work with !p.multi.
```

```
    p_nx=!p.multi[1]
```

```
    if p_nx eq 0 then p_nx=1
```

```
    p_ny=!p.multi[2]
```

```
    if p_ny eq 0 then p_ny=1
```

```
    ; Get the x/y position of the current window
```

```
    p_fx=!p.multi[0] mod p_nx
```

```
    if p_fx eq 0 then p_fx = !p.multi[1]
```

```
    p_fy=fix((!p.multi[0]-1) / (1.*p_nx))
```

```
    if !p.multi[0] eq 0 then p_fy= p_ny-1; !p.multi[0]=0 means this is the first plot on a new page
```

```
    print,!p.multi[0],p_fx,p_fy
```

```
    start_x=1.-(1.*p_fx)/!p.multi[1]
```

```
    end_x=start_x+1./!p.multi[1]
```

```
    start_y=(1.*p_fy)/!p.multi[2]
```

```
    end_y=start_y+1./!p.multi[2]
```

```
    print,start_x,end_x,start_y,end_y
```

```
    polyfill, [start_x,end_x,end_x,start_x,start_x],
[start_y,start_y,end_y,end_y,start_y],/normal,color=i+1
```

```
nplots = !P.multi(1) * !P.multi(2)
advance = nplots gt 1
map_set,advance=advance
```

```
endfor
```

```
end
```

The first section of the loop basically sets up the normalised x/y coordinates for this plot among the set of (here 7*5=25) plots. These coordinates are then printed to the screen using the print command, and all look correct. So, if I run this I'd expect to get 35 differently-coloured plots (well, map_set borders), in different shades of 'greenness' according to colour table 2, going across the window in rows from top to bottom.

However, what actually happens is that the first plot has a black background, rather than the initial dark green. The other 34 look as expected. If I insert a stop before the map_set command, I see that the dark green polygon is drawn but then erased by the first map_set call. No problem, I thought, I'll check if this is the first plot on the page and if so use the noerase keyword:

```
noerase=0
if !p.multi[0] eq 0 then noerase=1
nplots = !P.multi(1) * !P.multi(2)
advance = nplots gt 1
map_set,advance=advance,noerase=noerase
```

However, this gives the same behaviour. If I abandon maps for a moment and replace that section with this, it works fine:

```
noerase=0
if !p.multi[0] eq 0 then noerase=1
plot,findgen(4),noerase=noerase
if !p.multi[0] eq 0 then !p.multi[0] = !p.multi[1]*!p.multi[2]-1
```

... but I can't make it work with map_set at all. Can anyone see what I am doing wrong? This is IDL 8.2.2 on CentOS (not sure which version).

Thanks,

Andy
