

---

Subject: Re: Issue with long integer arrays

Posted by [Helder Marchetto](#) on Tue, 17 Dec 2013 19:42:49 GMT

[View Forum Message](#) <> [Reply to Message](#)

---

On Tuesday, December 17, 2013 8:20:38 PM UTC+1, do...@mail.usf.edu wrote:

> I should know this, but am having trouble with the following:  
>  
>  
>  
> I have several long integer(long) arrays that are restored into the workspace.  
>  
>  
>  
> I want to define an array so that my long arrays can be used in a loop later in my program.  
>  
>  
>  
> array1=long[25248]  
>  
> array1=long[2905]  
>  
> array1=long[4651]  
>  
> array1=long[4988]  
>  
>  
>  
> These are masks used to extract different regions of an image.  
>  
>  
>  
> How can I put the arrays into one variable that can be called in a loop?  
>  
>  
>  
> It should be simple, but I'm stumped. Thanks,  
>  
>  
>  
> Dan

There are more ways of doing this and depend on thing such as if you know the sizes before hand and so on. So I'll offer one and might not just be the best for your case, but I hope it helps.

```
pa = ptrarr(4,/allocate_heap)
*pa[0]=long[25248]
*pa[1]=long[2905]
*pa[2]=long[4651]
```

```
*pa[3]=long[4988]
```

```
For i=0,3 do begin  
    ;your work  
    print, mean(*pa[i])  
endfor
```

If you know the sizes before hand, one other solution would be to make one array long as the 4 together and then subscript the array.

Cheers,  
Helder

---