
Subject: Re: 3D point cloud visualization: filled polygons in the front, different fill colour + lines in the back

Posted by [Nuno Ferreira](#) on Mon, 25 May 2015 18:10:47 GMT

[View Forum Message](#) <> [Reply to Message](#)

And there was another error, sorry (wrong version...)! Here is the right version:

```
PRO question_example_event, ev
; (not really needed for this example)
END
```

```
PRO question_example
; create a test object
vertices = [[0, 0, 0], [1, 0, 0], [1, 1, 0], [0, 1, 0], [0.5, 0.5, 1]]
connectivity = [3, 0, 1, 4, $
               3, 1, 2, 4, $
               3, 2, 3, 4, $
               3, 3, 0, 4]
vert_colors = [[0,0,0],[255,0,0],[0,255,0],[0,0,255],[255,255,255]]
```

```
; Initialize model for display (2 views).
oModel1 = OBJ_NEW('IDLgrModel')
oModel2 = OBJ_NEW('IDLgrModel')
```

```
; Initialize polygon and/or polyline
option=3
CASE option of
```

```
1:  begin
    oPolygon = OBJ_NEW('IDLgrPolygon', vertices, $
        POLYGONS = connectivity, SHADING=1, $
        vert_colors=vert_colors)
    oPolyline = OBJ_NEW('IDLgrPolyline', vertices, $
        POLYLINES = connectivity, COLOR = [0, 0, 0])
end
```

```
2:  begin
    oPolygon = OBJ_NEW('IDLgrPolygon', vertices, $
        POLYGONS = connectivity, SHADING=1, $
        vert_colors=vert_colors, bottom=[200,200,200], $
        depth_offset=1)
    oPolyline = OBJ_NEW('IDLgrPolyline', vertices, $
        POLYLINES = connectivity, COLOR = [0, 0, 0])
end
```

```

3:  begin
    oPolygon = OBJ_NEW('IDLgrPolygon', vertices, $
      POLYGONS = connectivity, SHADING=1, STYLE=2, $
      vert_colors=vert_colors, bottom=[200,200,200], $
      depth_offset=1)
    oPolygon2 = OBJ_NEW('IDLgrPolygon', vertices, $
      POLYGONS = connectivity, SHADING=1, STYLE=1, $
      vert_colors=vert_colors, $
      depth_offset=0)
  end
endcase

; Add the polygon(s) and/or polyline to the model.
oModel1 -> Add, oPolygon
if option EQ 1 or option EQ 2 then oModel1 -> Add, oPolyline
if option EQ 3 then oModel1 -> Add, oPolygon2
oModel2.Add, oModel1, /alias ; create an alias for 2nd model

; used for display:
ov1 = idlgrview(viewplane_rect=[-2, -2, 4, 4], zclip=[2, -2], eye=2.1)
ov1.add, oModel1
ov2 = idlgrview(viewplane_rect=[-2, -2, 4, 4], zclip=[2, -2], eye=2.1)
ov2.add, oModel2

; create GUI
s = 256
base = widget_base(/row, Title='Option '+string(option))
d1 = widget_draw(base, graphics_level=2, xsize=s, ysize=s, tooltip="Front")
d2 = widget_draw(base, graphics_level=2, xsize=s, ysize=s, tooltip="Back")

; show GUI and model
widget_control, base, /realize
widget_control, d1, get_value=ow1
widget_control, d2, get_value=ow2
oModel1 -> Rotate, [1, 0, 0], 45 ; Rotate to better show the front side
ow1.setproperty, graphics_tree=ov1
ow1.draw
oModel1 -> Rotate, [1, 0, 0], 180 ; Rotate again to show the back side
ow2.setproperty, graphics_tree=ov2
ow2.draw

xmanager, 'question_example', base
END

```
