Subject: Re: Which "PATH" did IDL use???
Posted by deepeyes.ym on Thu, 30 Jul 2015 09:09:24 GMT
View Forum Message <> Reply to Message

On Wednesday, July 29, 2015 at 11:49:56 PM UTC+3, Doug Edmundson wrote: > On 7/29/15 3:33 AM, wrote: >> I'm really confused about all the parameters inside of IDL. >> I have called "spawn" by using >> >> IDL> spawn, 'gv m4 r 600 test flag0 individual outliers.eps' >> bash: gv: command not found >> >> Then, >> >> IDL> PRINT, GETENV ("PATH") >> /Applications/itt/idl71//bin:/usr/bin:/bin:/usr/sbin:/sbin >> BUT, I don't know where this "PATH" comes from!!!! >> >> It's different from the "!PATH" inside of IDL, different from the "\$PATH" > in the .bash profile, so where IDL get this parameter and how could I change > this one???? >> >> any comments will be appreciated! > > Hi deepeyes, > I'll guess that in your case it's using .bashrc to set the environment. It will not be using IDL's environment since a new "bash" shell is being created. So, try updating PATH in .bashrc. > > Cheers, > Doug Actually, I'm using IDLDE, that's why the .bash profile not working (I have already defined the

Actually, I'm using IDLDE, that's why the .bash_profile not working (I have already defined the PATH in .bash_profile)