Subject: Re: Which "PATH" did IDL use??? Posted by deepeyes.ym on Thu, 30 Jul 2015 19:24:50 GMT

View Forum Message <> Reply to Message

On Wednesday, July 29, 2015 at 12:33:32 PM UTC+3, deepe...@gmail.com wrote:

- > I'm really confused about all the parameters inside of IDL.
- > I have called "spawn" by using

>

- > IDL> spawn, 'gv m4\_r\_600\_test\_flag0\_individual\_outliers.eps'
- > bash: qv: command not found

>

> Then,

>

- > IDL> PRINT, GETENV ("PATH")
- > /Applications/itt/idl71//bin:/usr/bin:/bin:/usr/sbin:/sbin

>

> BUT, I don't know where this "PATH" comes from!!!!

>

> It's different from the "!PATH" inside of IDL, different from the "\$PATH" in the .bash\_profile, so where IDL get this parameter and how could I change this one????

>

> any comments will be appreciated!

## Dear all,

thank you very much for all your help. With suggestion from Doug, I finally be able to solve this problem. First of all, I'm sorry that I forget to mention I'm using Mac OSX 10.11 public beta 3 and IDL v7.1.1. This problem not appears in 10.10.4. So, may be Apple changes something. The solution is that just COPY .bash\_profile to .bashrc, since OSX don't have the .bashrc in the first place (also I have already set the \$PATH in .bash\_profile, that's why it is ok when using idl in terminal). It's seems that IDLDE v7 only recognizes the .bashrc.