
Subject: Re: Changing variable type

Posted by [Helder Marchetto](#) on Mon, 16 May 2016 13:12:00 GMT

[View Forum Message](#) <> [Reply to Message](#)

On Monday, May 16, 2016 at 1:51:18 PM UTC+1, Mats Löfdahl wrote:

> Den måndag 16 maj 2016 kl. 14:37:24 UTC+2 skrev Helder:

>> On Monday, May 16, 2016 at 1:19:53 PM UTC+1, Mats Löfdahl wrote:

>>> Den måndag 16 maj 2016 kl. 13:34:52 UTC+2 skrev Helder:

>>>> On Monday, May 16, 2016 at 12:31:45 PM UTC+1, Helder wrote:

>>>> > On Monday, May 16, 2016 at 11:43:54 AM UTC+1, Mats Löfdahl wrote:

>>>> > > Is there a way in IDL to change the type of an array, specifically a 16-bit integer into a 16 bit unsigned integer?

>>>> > >

>>>> > > No, I do not mean `b = uint(a)`. This makes a new array and keeps the values. I want to change the variable type of the existing array (from 2 to 12), so the bit values are interpreted differently. Is this possible?

>>>> > >

>>>> > > /Mats

>>>> >

>>>> > Hi Mats,

>>>> > I think you're looking for the `offset` keyword in the `uint` function, but I'm not 100% sure (because this also makes a copy of the variable... there is no `/temporary` keyword)

>>>> >

>>>> > IDL> a = -1

>>>> > IDL> help, a

>>>> > A INT = -1

>>>> > IDL> print, uint(a,0)

>>>> > 65535

>>>> >

>>>> > Would this do what you want?

>>>> >

>>>> > Cheers,

>>>> > Helder

>>>>

>>>> Sorry, you wanted an array, so you have to do this:

>>>> IDL> a = indgen(20)

>>>> IDL> a[10:19] = -indgen(10)

>>>> IDL> a

>>>> 0 1 2 3 4 5 6 7 8 9 0 -1 -2 -3 -4 -5
 -6 -7 -8 -9

>>>> IDL> print, uint(a,0,20)

>>>> 0 1 2 3 4 5 6 7 8 9 0 65535 65534 65533
65532 65531 65530 65529 65528 65527

>>>>

>>>> Does it make sense?

>>>>

>>>> Cheers,

>>>> Helder

>>>
>>> I'd like to avoid making new variables if possible.
>>>
>>> I guess I was thinking that IDL variables in reality were some sort of objects, and there would be methods that just change the type property. Or something like that.
>>
>> Well, there's the `idl_variable` method `convert`:
>> `a.convert(type=12)`
>> but it also creates a new variable.
>>
>> I don't see another way around unless you use some DLL trick to modify the variable internally. But maybe some IDL gurus know more about this stuff... I never ventured beyond using the offset options.
>>
>> Cheers,
>> Helder
>
> Oh, that looks almost like what I envisioned! Thanks! Where can I read about these methods? I tried searching for "variable methods" in www.harrisgeospatial.com/docs but the hits don't look like they would lead to a list of such methods.
>
> Anyway, I believe what would be needed is a procedure form of that method. So one could do
>
> `a.convert, type=12`
>
> (I tried it, doesn't work in IDL 8.5.1...)

Hi,
I obviously tried the `convert` method as a procedure call, but didn't work :-)

Cheers,
Helder
