
Subject: Re: File units (de)allocation in IDL - what is the proper way?

Posted by [Helder Marchetto](#) on Fri, 22 Jul 2016 09:51:03 GMT

[View Forum Message](#) <> [Reply to Message](#)

On Friday, July 22, 2016 at 11:05:09 AM UTC+2, Dave wrote:

> Hello everyone,
> when opening files to write outputs I usually do:
>
> OPENW, unit1, 'file1.txt', /GET_LUN
> OPENW, unit2, 'file2.txt', /GET_LUN
> ...
> CLOSE, unit1
> CLOSE, unit2
>
> FREE_LUN, unit1
> FREE_LUN, unit2
>
> However, it seems that closing *and freeing* can be equally achieved with:
>
> CLOSE, unit1, unit2, /ALL
>
> Is this correct? Is there a best practice?
> Thanks in advance.
> Dave

I don't think so.

These commands:

```
CLOSE, unit1  
CLOSE, unit2
```

are the same as

```
CLOSE, unit1, unit2
```

But this command could do much more:

```
CLOSE, unit1, unit2, /all
```

In fact it will close *all* open units. And you don't need to specify the units at all. In other words it is equivalent to:

```
CLOSE, /ALL
```

Now you should see the problem: If you have other units open, this will close them. So it is only useful if you lost track of open units and you want to close them all... Otherwise you might close units that you don't want to close at all.

I hope this helps.

Cheers,
Helder
